

Standalone Access Control System		Standard Packing: 50 pcs / carton	10 pcs	50 pcs	100 pcs
UK3-3	 <b>HOT</b>	<b>Access Control Keypad with Built-in Card Reader</b> Card Type: 125KHz EM card Multi-function, operating as access control or card reader, suitable for various occasions. The unit accepts up to 500 users, allow entry via a 4-6 digits PIN and/or by presenting a proximity EM card Operating voltage range: DC12-24V Low power consumption (standby input current: <20mA)	\$17.00	\$15.00	\$14.00
U30EM		<b>Plastic standalone access control keypad</b> Working voltage:12-24V DC digits backlit keypad Capacity: 2000 users <b>Wiegand 26 input for the connection of an external reader</b> Color: white and black Size: 92*81*20mm 0.2KGS	\$20.00	\$18.00	\$17.00
U3EH		<b>Plastic standalone access control without keypad</b> Non-waterproof plastic case Large capacity:10000 card users Add and delete user via mastercard / remote control Color: white and black Size:115*56*22 mm 0.4KGS	\$25.00	\$23.00	\$22.00
U3EH-W		<b>Waterproof 0.45KGS</b>			
U31EM		<b>Plastic standalone access control keypad</b> Working voltage:12-24V DC digits backlit keypad Capacity: 2000 users <b>Wiegand 26 input for the connection of an external reader</b> Color: white and black Size: 96*73*20mm 0.2KGS	\$20.00	\$18.00	\$17.00
UK4-2	 <b>NEW</b>	<b>Access Control Keypad with Built-in Card Reader</b> Card Type: 125KHz EM card Super low power consumption, the standby current is 14±5mA;Supply Voltage: 12V±10% DC Anti-magnetic.2,000 users. 3 access modes: Card, Card or PIN, Card with PIN Wiegand 26 input & output, can work as Wiegand reader/Controller; Interlock, Anti-passback	\$22.00	\$20.00	\$19.00
U5EM	 <b>HOT</b>	<b>Metal standalone access control keypad</b> Indoor use With doorbell button,can connect any doorbell Working voltage:12-24V DC Zinc Alloy case anti-vandal digits backlit keypad Capacity: 2,000 users Size:110*75*25(mm) 0.6KGS	\$23.00	\$21.00	\$20.00
U6EM	 <b>NEW</b>	<b>Metal standalone access control keypad</b> Indoor use With doorbell button, can connect any doorbell Working voltage:12-24V DC Zinc Alloy case anti-vandal digits backlit keypad Capacity:2,000 usersSize:86*86*23(mm) 0.6KGS	\$38.00	\$36.00	\$35.00
U6EM-W		<b>Waterproof IP68 outdoor use 0.7KGS</b>	\$42.00	\$40.00	\$39.00
U8EM-W (EM125Khz)		<b>Metal standalone access control keypad</b> <b>Waterproof IP68 outdoor use</b> With doorbell button, can connect any doorbell Working voltage:12-24V DC Zinc Alloy case anti-vandal digits backlit keypad Capacity: 2,000 users	\$39.00	\$37.00	\$36.00
U8MF-W (Mifare13.56Mhz)			\$43.00	\$41.00	\$40.00
U603EM		<b>Metal standalone access control keypad</b> Working voltage:12-24V DC Indoor use With doorbell button, can connect any doorbell Zinc Alloy case anti-vandal Luminous keyboard Capacity: 2,000 users Can connect external reader Size:123*58*20(mm) 0.47KGS	\$27.00	\$25.00	\$24.00
U603EM-W		<b>Waterproof IP68 outdoor use 0.52KGS</b>	\$30.00	\$28.00	\$27.00

UW2			<b>Waterproof access control / Reader card</b> Static Current: $\leq 15\text{mA}$ , Very low power consumption Anti-Magnetic: Preventing access by strong magnetic object <b>Large Capacity: 10,000 users</b> Manage Card: the manage card can add/delete the users directly, very convenient High Speed Search: filled with 10000 users, the search time $< 0.15$ seconds Wiegand 26 input & output, can work as Wiegand reader/Controller Interlock, Anti-passback	\$37.00	\$35.00	\$34.00
UW2-A			125KHz EM&HID card, Support adding 999 cards with serial numbers once	\$39.00	\$37.00	\$36.00
UW1-A			<b>Metal Waterproof Two-door access control</b> Backlight keypad ; <b>Two-relay operation</b> Up to 1,200 users (Zone 1:1,100 users & Zone 2:100 users) Card Type: 125KHz EM, PIN length: 4-8 digits 3 access modes: Card, Card or PIN, Card with PIN; Operating Voltage: 12-18V AC/12-24V DC	\$55.00	\$53.00	\$51.00
UW1-B			Backlight keypad, convenient for operating in night; Large capacity: 2,500 users Card Type: 125KHz EM, PIN length: 4 digits 3 access modes: Card, Card or PIN, Card with PIN; Operating Voltage: 12-18V AC/12-24V DC Wiegand 26 input & output, can work as Wiegand reader / Controller; Machine code setting: 1-255 can be set as facility codes	\$54.00	\$52.00	\$50.00
UW3-A			<b>Metal Waterproof Two-door access control</b> Backlight keypad ; <b>Two-relay operation</b> Up to 1,200 users (Zone 1:1,100 users & Zone 2:100 users) Card Type: 125KHz EM, PIN length: 4-8 digits 3 access modes: Card, Card or PIN, Card with PIN; Operating Voltage: 12-18V AC/12-24V DC	\$56.00	\$54.00	\$52.00
UW3-B			Backlight keypad, convenient for operating in night; Large capacity: 2,500 users Card Type: 125KHz EM, PIN length: 4 digits 3 access modes: Card, Card or PIN, Card with PIN; Operating Voltage: 12-18V AC/12-24V DC Wiegand 26 input & output, can work as Wiegand reader/Controller Machine code setting: 1-255 can be set as facility codes	\$55.00	\$53.00	\$51.00
UW3-H			Support HID Card; PIN length: 4-8 digits	\$56.00	\$54.00	\$52.00
UW3-M			Support Mifare Card; PIN length: 4-8 digits	\$60.00	\$58.00	\$56.00
UF-01			Metal shell, Simple & fashion design with <b>fingerprint recognition</b> Adopt the dark background fingerprint imaging technique, with stronger adaptability. Fingerprints capacity:1000, suitable for office, villa, household etc. Input voltage: DC12~24V Multi-usage, all kinds of functions integrated to one, controller & reader, operation is very simple Touch the luminous button unlock the function of fingerprint; manually or automatically enter a dormant state. <b>Infrared remote control</b> and administrator's fingerprint Anti tamper alarm function.	\$75.00	\$72.00	\$68.00
UF1			Metal <b>Fingerprint</b> access control <b>indoor use</b> DC12V Zinc alloy case 1000 users add users through <b>remote control, masterfingerprint, support fingerprint only</b> Standalone reader or connect with control panel 110*75*30mm 0.55KGS	\$65.00	\$62.00	\$58.00
UF1-EM			support EM125Khz card and fingerprint2000 card user, 1000 fingerprintuser	\$68.00	\$65.00	\$61.00
<b>Proximity Card Reader (125Khz or 13.56Mhz) Standard Packing: 100 pcs / carton</b>				<b>10 pcs</b>	<b>50 pcs</b>	<b>100 pcs</b>
R08H			Passive RFID Proximity Card Reader Wiegand 26/34 Output 126*76*23(mm).9~16V, 50mA, 5~10cm proximity range.100m communication distance.water-proof <b>Mifare reader ( add 3 USD )</b>	\$8.00	\$7.00	\$6.00
R701A			Passive RFID Proximity Card Reader Wiegand 26/34 Output 126*86*23(mm).9~16V, 50mA, 5~15cm proximity range.100m communication distance.water-proof <b>Mifare reader ( add 3 USD )</b>	\$9.00	\$8.00	\$7.00

R702A		Plastic RFID Card Reader Wiegand 26/34 Output Less than 0.2 second Response Speed Proximity Time Distance: 5-10cm Proximity Range ; Support 125 kHz ID Card <b>Mifare reader ( add 3 USD )</b>	\$12.00	\$11.00	\$10.00
R801A		Hot Selling RFID Card Reader Wiegand 26/34 /ABA Standard Format Data Output Less than 0.2 second Response Speed Less than 0.5 seconds Proximity Time Distance: 2-15cm Proximity Range Support UEM 4100 ID Card or compatible with it <b>Mifare reader ( add 3 USD )</b>	\$9.00	\$8.00	\$7.00
R203A		86*86*18(mm) 9~16V,50mA,5~10cm Wiegand 26/34 Output proximity range.100m communication distance.water-proof,NEW <b>Mifare reader ( add 3 USD )</b>	\$10.00	\$9.00	\$8.00
R401A		100*100*20(mm) 9~16V,50mA,5~10cm Wiegand 26/34 Output proximity range.100m communication distance.water-proof,NEW! Black Color <b>Mifare reader ( add 3 USD )</b>	\$11.00	\$10.00	\$9.00
R602A		88*88*18(mm) 9~16V,50mA,5~10cm Wiegand 26/34 Output proximity range.100m communication distance.water-proof,NEW! Black Color <b>Mifare reader ( add 3 USD )</b>	\$12.00	\$11.00	\$10.00
R502A		>100*100*22(mm) 9~16V,50mA,5~10cm >Wiegand 26/34 Output >proximity range.100m communication distance. <b>waterproof</b> > <b>Mifare reader ( add 3 USD )</b>	\$16.00	\$15.00	\$14.00
R2EM ( EM card )		<b>Waterproof</b> RFID Reader >Output interface: Wiegand26 bits >3 Color LED display for the working condition: yellow, green, red > <b>Weatherproof, shockproof, anti-vandal</b> >Reading distance: 3-10CM >Working frequency: 125KHz(EM,HID card),13.65MHz(Mifare card) >Transmit distance: 100M >Operating voltage: 12V DC	\$22.00	\$20.00	\$19.00
R2-H ( HID card )			\$23.00	\$21.00	\$20.00
R2-H&EM (EM&HID card)			\$24.00	\$22.00	\$21.00
R2-M ( Mifare card )			\$26.00	\$24.00	\$23.00
R08Z		<b>Car parking reader</b> Wiegand 26/34, RS485/232 Special EM-ID Middle Range Card <b>1M Proximity range,widely used for Car Parking.</b> 230*230*35(mm) 12V,150mA, 100m communication distance.	\$60.00	\$57.00	\$55.00

Electric Silent Lock Series		Standard Packing: 50 pcs / carton	10 pcs	50 pcs	100 pcs
UT06-A		<b>Outer-mute lock</b> Lock Size: 131.5 * 99.5 * 42.5 Rated voltage: DC12V Working Current: 1.5A (instantaneous current) Life: 500,000 times Lock mode: collision type lock Features: Ultra-quiet, no need to distinguish between left and right, unlock signal line regardless of the positive and negative	\$16.00	\$15.00	\$14.00
UT06-B		<b>Inner-mute lock</b> Lock Size: 131.5 * 99.5 * 42.5 Rated voltage: DC12V Working Current: 1.5A (instantaneous current) Life: 500,000 times Lock mode: collision type lock Features: Ultra-quiet, no need to distinguish between left and right, unlock signal line regardless of the positive and negative	\$16.00	\$15.00	\$14.00
UT06-S		<b>Double-mute lock</b> Lock Size: 131.5 * 99.5 * 42.5 Rated voltage: DC12V Working Current: 1.5A (instantaneous current) Life: 500,000 times Lock mode: collision type lock Features: Ultra-quiet, no need to distinguish between left and right, unlock signal line regardless of the positive and negative	\$18.00	\$17.00	\$16.00
UT06-F		<b>Anti-tamper lock</b> Lock Size: 131.5 * 99.5 * 42.5 Rated voltage: DC12V Working Current: 1.5A (instantaneous current) Life: 500,000 times Lock mode: collision type lock Features: Ultra-quiet, no need to distinguish between left and right, unlock signal line regardless of the positive and negative	\$17.00	\$16.00	\$15.00
Smart Electromotored Lock Series		Standard Packing: 50 pcs / carton	10 pcs	50 pcs	100 pcs
UT06-DC		<b>Single-head card integrated motor lock</b> Lock Size: 131.5 * 99.5 * 42.5mm life: more than 500,000 times; Lock mode: induction lock Features: closed automatically locked, without distinction installation direction of the door Surface Technology: Brushed nickel Operating voltage: DC12V optional ID card, IC card, can be equipped with remote unlocking function; Working current: ≤350mA; Quiescent Current: 15mA Capacity: 1000 (can be customized to 10,000 capacity)	\$33.00	\$31.00	\$30.00
UT06-DCS		<b>Double card integrated motor lock</b> Lock Size: 131.5 * 99.5 * 42.5mm life: more than 500,000 times; Lock mode: induction lock Features: closed automatically locked, without distinction installation direction of the door Surface Technology: Brushed nickel Product Weight: 1.5KG Operating voltage: DC12V optional ID card, IC card, can be equipped with remote unlocking function; Working current: ≤350mA; Quiescent Current: 15mA Capacity: 1000 (can be customized to 10,000 capacity)	\$35.00	\$33.00	\$32.00
Electric Rim Lock Series		Standard Packing: 50 pcs / carton	12.50	11.00	10.00
UT7013		Lock Size: 126 * 102 * 34.5 Rated voltage: DC12V <b>Stainless steel-Double cylinder</b> Closed Way: Lock by collision; Finishing: SS Features: no need to distinguish between left and right, unlock signal line regardless of the positive and negative	\$25.00	\$23.00	\$22.00
UT2015		Lock Size: 126 * 102 * 34.5 Rated voltage: DC12V <b>White Nickel</b> Closed Way: Lock by collision; Finishing: Power Features: no need to distinguish between left and right, unlock signal line regardless of the positive and negative Salt test: 24 hours	\$23.00	\$21.00	\$20.00
UT7018		Lock Size: 126 * 102 * 34.5 Rated voltage: DC12V <b>Black Powder</b> Closed Way: Lock by collision; Finishing: SN Features: no need to distinguish between left and right, unlock signal line regardless of the positive and negative Salt test: 24 hours	\$22.00	\$20.00	\$19.00
Electric Strikes Lock		Standard Packing: 50 pcs / carton	10 pcs	50 pcs	100 pcs

US-131		<b>Narrow-type Electric Strike</b> Lock Size: 160Lx25Wx31H(mm) Holding Strength: 800kg Voltage: 12VDC Current: 450mA Feature: Fail Secure(NO); Fail Safe(NC) Surface Temperature: Within +20℃ Face plate Housing: Electroplating Suitable For: Wooden Door, Metal Door, PVC Door Opening Mode: 90 Degree Swinging Door Function: Built-out MOV Weight: 0.36kg <b>Optional Mechanical Lock: US-307</b>	\$12.00	\$9.00	\$8.80
US-307		Lock Size: 175Lx25Wx44H(mm) Holding Strength: 1000kg <b>Suitable For: US-131NO/NC</b> Security: Open the door with key or hand in emergency Opening Mode: 90 degree inswing door Suitable For: Wooden Door, Metal Door, PVC Door Material: Stainless Steel Weight: 1kg	\$28.00	\$24.00	\$23.00
US-132		<b>Long-type Electric Strike</b> Lock Size: 250Lx25Wx31H(mm) Holding Strength: 800kg Voltage: 12VDC Current: 200mA Feature: Fail Secure(NO); Fail Safe(NC) Surface Temperature: Within +20℃ Face plate Housing: Electroplating Suitable For: Wooden Door, Metal Door, PVC Door Opening Mode: 90 Degree Swing Door Function: Built-out MOV Weight: 0.4kg <b>Optional Mechanical Lock: US-308</b>	\$16.00	\$13.00	\$12.00
US-308		Lock Size: 175Lx25Wx44H(mm) Holding Strength: 1000kg <b>Suitable For: US-132 NO/NC</b> Security: Open the door with key or hand in emergency Opening Mode: 90 degree inswing door Suitable For: Wooden Door, Metal Door, PVC Door Material: Stainless Steel Weight: 1kg	\$33.00	\$29.00	\$28.00
<b>Electric Bolt Lock Series</b>		<b>Standard Packing: 50 pcs / carton</b>	<b>10 pcs</b>	<b>50 pcs</b>	<b>100 pcs</b>
EB-100		<b>Fail safe simple electric bolt</b> Face Plate: 205Lx35Wx41.5H(mm) Strike: 90Lx25Wx2H(mm); Bolt: 16mm; Voltage: 12VDC Start Current: 900mA; Standby Current: 100mA Solid Bolt: Polishing housing, 800Kg Holding Force Suitable For: Woodeng Door, Glass Door, Metal Door; Induction Distance: 8mm Face Place Material: High Aluminum, Carrulous Line Finished Weight: 0.7kg	\$19.00	\$16.00	\$15.00
EB-200		<b>Low Temperature Fail Safe Electric Bolt</b> W/Signal Time Delay (0,3,6,9 sec.) & LED Lock body dimensions: length 200 x width 28x thickness 38mm) Operating voltage: 12VDC + 10% range (24VDC can be set); Start Current: 900mA (instant start) Working Current: 120mA (fully locked) Cylinder strength: hardened stainless steel solid cylinders, to withstand the impact of 1000kg Selection of door type: wooden doors, glass doors, metal doors, PVC doors	\$26.00	\$23.00	\$22.00
<b>Magnetic Lock and Brackets Series</b>		<b>Standard Packing: 50 pcs / carton</b>	<b>10 pcs</b>	<b>50 pcs</b>	<b>100 pcs</b>
UM-280		<b>Surface Mounted</b> ; Size: 250Lx48.5Wx25H(mm) Case: Aluminum alloy; Weight: 2.1 KG For wooden door, Glass door, Metal door, etc DC12V 380mA; <b>Signal Output and LED</b> Holding force: 280kg/600lb	\$18.00	\$16.00	\$15.00
UM-280-T		with 0,3,6,9 secs Delay function	\$26.00	\$24.00	\$22.00
UM-280-W		<b>Waterproof Design</b>	\$25.00	\$23.00	\$20.00
UM-280D		<b>Double Door Surface Mounted</b> Case: Aluminum alloy; Size: 500Lx48.5Wx25H(mm) Weight: 4.2 KG For wooden door, Glass door, Metal door, etc; DC12V, 380mA; <b>Signal Output and LED</b> Holding force: 560kg/1200lb	\$47.00	\$45.00	\$43.00
UM-280D-T		with 0,3,6,9 secs Delay function	\$52.00	\$49.00	\$47.00



UC-280		<b>Conceal Mounted</b> ; Holding force: :280kg/600lb Case: Aluminum alloy; Size:250*47*25mm DC12V 480mA For wooden door, Glass door, Metal door, etc;Weight:2.0kg DC12V 480mA ; <b>Signal Output</b>	\$19.00	\$18.00	<b>\$17.00</b>
UM-350		Surface Mounted; Size:285Lx55Wx27.5H(mm) Case: Aluminum alloy; Work current:480mA Weight: 2.7 KG For wooden door, Glass door, Metal door, etc Power on to lock, <b>Status signal NO/NC output and LED</b> Holding force:350kg/800lb	\$34.00	\$32.00	<b>\$30.00</b>
UM-350-T		with 0,3,6,9 secs Delay function	\$36.00	\$34.00	<b>\$32.00</b>
UM-500		Surface Mounted;Size:265Lx71.8Wx38.8H(mm) Case: Aluminum alloy;Work current:420mA Weight: 4.5 KG For wooden door, Glass door, Metal door, etc <b>Status signal NO/NC; LED</b> Holding force:500kg/1200lb	\$46.00	\$44.00	<b>\$42.00</b>
UM-500-T		with 0,3,6,9 secs Delay function	\$52.00	\$49.00	<b>\$47.00</b>
UM-280-ZL		Z L bracket, 0.5KG three parts <b>for UM-280</b>	\$8.95	\$7.95	<b>\$6.95</b>
UM-350-ZL		Z L bracket, 0.5KG three parts <b>for UM-350</b>	\$11.00	\$9.00	<b>\$8.00</b>
UM-500-ZL		Z L bracket, 0.5KG three parts <b>for UM-500</b>	\$16.00	\$14.00	<b>\$13.00</b>
UM-280-U		U Type Magnetic Lock Bracket 180mm×28mm×41mm 0.35 KG <b>for UM-280</b>	\$4.95	\$3.95	<b>\$3.45</b>
UM-350-U		U Type Magnetic Lock Bracket 180mm×28mm×42mm 0.38KG <b>for UM-350</b>	\$5.95	\$4.95	<b>\$4.45</b>
<b>Door Exit Switch Buttons</b>		<b>Standard Packing: 100 pcs / carton</b>	<b>10 pcs</b>	<b>50 pcs</b>	<b>100 pcs</b>
E6-S NO/NC/COM		Dimensions: 86Lx86Wx20H(mm) Standard Structure: Fireproof Material Output Contact: <b>NO/NC/COM</b> Weight: 0.075kg, Standard Packing: 100pcs Optional Accessories:M86 Mounted Back Box	\$2.00	\$1.50	<b>\$1.00</b>
M6 Surface Mount NO/COM		Dimensions: 86Lx86Wx25H (mm) Standard Structure: Fireproof Material Output Contact: <b>NO/COM</b> Weight: 0.075kg Standard Packing: 100pcs Installation: <b>Surface Mount</b>	\$2.00	\$1.50	<b>\$1.20</b>
T6		Dimensions: 86Lx86Wx25H (mm) With a <b>luminous indication</b> Output Contact: <b>NO/NC/COM</b> Weight: 0.095kg Standard Packing: 100pcs	\$2.50	\$2.00	<b>\$1.50</b>
P86 Plastic bottom box		<b>Surface mounted back box 86 * 86</b> Suitable for installation of all 86 plastic switch Size: 86 * 86MM, 60MM screw hole size Weight: 0.065Kg, 6.5KG / 100 / carton Suitable for <b>E6-S, T6</b>	\$1.00	\$0.80	<b>\$0.60</b>
M86		Dimensions: 86Lx86Wx26H(mm) Standard Instruction zinc alloy material,and surface is coated with chrome Weight 0.18kg <b>Suitable for all sizes 86 MM concealed out switch such as S2, T2,880M,C12</b>	\$4.50	\$4.00	<b>\$3.50</b>
DB12		12VDC Wired Door Bell It can be powered directly from the access control panel, convenient and practical. 4 Line Weight: 0.085Kg	\$6.00	\$5.00	<b>\$4.00</b>
DB03		Dry battery Wired Door Bell Battery-powered (three AA batteries) 2 Line Weight: 0.105Kg	\$5.00	\$4.00	<b>\$3.00</b>
S2 No Touch (Infrared Sensor)		Dimensions: 86Lx86Wx29H(mm) Output Contact: <b>NO/NC/COM</b> Suitable for Door: Hollow Door Detection range 5-15cm Adjustable LED Indicator:Blue LED indicator: standby GREEN LED indicator: sensation Weight: 0.148kg	\$8.50	\$7.50	<b>\$6.50</b>
T2 Touch Exit		Dimensions: 86Lx86Wx20H(mm) / 86Lx50Wx20H(mm) Output Contact: NO/NC/COM Installation: Surface Mount LED Indicator:Blue LED indicator: standby GREEN LED indicator: sensation Weight: 0.12kg / 0.10kg	\$9.50	\$8.00	<b>\$7.00</b>

805LS Metal surface mounted switch			Size: 80x30x24mm, normally open NO output, suitable for ultra-narrow Box installation 4 lines <b>(12V / GND / NO / COM)</b> Blue LED lights. Material: zinc alloy, surface plating pearl Luo, silk hand and door symbols Installation: surface mounted Weight: 0.15Kg	\$10.00	\$9.00	<b>\$8.00</b>
880M Big mushroom button			Dimensions: 86Lx86Wx35H(mm) Standard Structure Stainless steel Panel Weight: 0.46kg Power: DC12V-24V Output Contact: <b>NO/NC/COM</b>	\$11.00	\$10.00	<b>\$9.00</b>
C12 Touch Exit			Dimensions: 86Lx86Wx25H(mm) / 86Lx50Wx25H(mm) Output Contact: <b>NO/NC/COM</b> Mechanical Life: 500000 tested Suitable for Door: Hollow Door Detection range: 0.1-10cm Weight: 0.12kg	\$13.00	\$12.00	<b>\$11.00</b>
809			Dimensions 86Lx86Wx50H(mm) Standard Structure Fireproof Material, Easy to install Output contact: <b>1NO/1NC/1COM</b> Suitable for Door 100000 tested Suitable for Exit Door, Emergence Door Optional Accessories: Glass, Cover Color: <b>Green, Red, White and yellow</b> Weight: 0.17kg	\$6.00	\$5.00	<b>\$4.00</b>
Glass Cover			Organic Glass Cover (Protection Cover)	\$0.60	\$0.50	<b>\$0.40</b>
Glass			Emergency Break Glass 75mm*40mm*1mm	\$0.38	\$0.35	<b>\$0.30</b>
808 Resettable With protective cover			Output contact: 2NO/2NC/2COM No need to replace the sheet glass Housing: ABS fireproof plastic Color: Green or Red FIRE Alarm return circuit: customized impedance Alarm glass: manual reset optional Operating voltage: 30VDC Operating current: 2A Withstood-voltage: 250V Operating temperature: -10℃-50℃ Size: 86*86*56mm Weight: 0.2kg	\$8.00	\$7.00	<b>\$6.00</b>
<b>Door Closer, Access Control Power Supply    Standard Packing: 50pcs/ Carton    10 pcs    50 pcs    100 pcs</b>						
DC10			High-quality Door Closer Suitable for door weight <b>45-75 KG</b> Max door wide: 900-1200 mm Weight: 2 KG	\$19.00	\$17.00	<b>\$15.00</b>
UPS-3A			AC220V±20%, <b>12V DC 3A</b> NC, NO, GND, +12V, PUSH, + Control; Delay control: 0-10 second	\$11.00	\$9.00	<b>\$8.00</b>
UPS-5A			AC220V±20%, <b>12V DC 5A</b> NC, NO, GND, +12V, PUSH, + Control; Automatic Protection Switching	\$13.00	\$12.00	<b>\$11.00</b>
UPSB-3A			AC220V±20%, <b>12V DC 3A</b> NC, NO, GND, +12V, PUSH, + Control; Delay control: 0-10 second	\$13.00	\$11.00	<b>\$10.00</b>
UPSB-5A			AC220V±20%, <b>12V DC 5A</b> Automatic Protection Switching; <b>12V 7 A battery back up Available</b>	\$15.00	\$13.00	<b>\$12.00</b>

Validity Date:	Jan 1, 2016 - June 30, 2016.      reserves the right to revise it
Shipping Terms:	Say US\$, FOB Shenzhen China for Bulk Order
Payment Terms:	T/T, Paypal, Western Union in Advance
OEM / ODM:	Available
Warranty Period:	2 years
Delivery Terms:	Sample Order: 1 - 3 Days ; General Order: 3 - 5 Days