

Photo	Model	Main Features	Specification	Unit Price (USD)	
				10-50 PCS	More than 50 PCS
Active Infrared Detectors					
	ABO-20L	<ul style="list-style-type: none">◆ Passed CE,FCC,ROHS,IP55 certification◆ Can be used with access control system,extensive use◆ Fully sealed design,rain-proof(fog),dust-proof(worm)◆ With high levels of anti-RFI/EMI capability◆ Professional anti-jamming optical housing	<ul style="list-style-type: none">◆ Outdoor alert distance:10m◆ Indoor alert distance:20m◆ Working voltage: DC12~24V◆ Operating temperature:-25℃~+55℃◆ Relay output:1A max 36V◆ Size:49.2*76*21.6mm◆ Packing:200PCS/Carton	\$8.00	\$7.00
	ABT-20	<ul style="list-style-type: none">◆ Passed CE,FCC,ROHS,IP55 certification◆ 2 beams active infrared detector	<ul style="list-style-type: none">◆ Working voltage:DC12~24V◆ Response speed:50~700msec◆ Alarm output:Relay contact output NO or NC;Contact capacity AC/DC30V 0.5Amax◆ Operating temperature:-25℃~+55℃◆ Horizontal angle adjustment:180 °?90 °◆ Vertical angle adjustment:°0 °◆ Size:171*82*77mm◆ Packing:20PCS/Carton	\$11.50	\$10.50
	ABT-30	<ul style="list-style-type: none">◆ Anti-glare up to 50,000 LUX, built-in automatic adjustment strong light filtering system			
	ABT-60	<ul style="list-style-type: none">◆ When faced with fog or inclement weather,the detector sensitivity will			
	ABT-80	<ul style="list-style-type: none">increase automatically(AGC circuit)			
	ABT-100	<ul style="list-style-type: none">◆ Up and down optical lens can adjust the mechanical design,making adjustments more faster,convenient and accurate.			
	ABE-50	<ul style="list-style-type: none">◆ Passed CE,FCC,ROHS,IP55 certification◆ New 3 beams active infrared detector	<ul style="list-style-type: none">◆ Working voltage:DC12 ~ 24V◆ Operating temperature: -25 ℃ ~ +55 ℃◆ Relative humidity: 5% ~ 95% (RH)◆ Tamper output:contact output NC; Contact rating:DC24V 0.5Amax◆ Horizontal angle adjustment:180 °?90 °◆ Vertical angle adjustment:°0 °◆ Material:PC◆ Size:240*88*85mm◆ Packing:12PCS/Carton	\$20.00	\$19.00
	ABE-100	<ul style="list-style-type: none">◆ Ten signal design, horizontal/vertical optical angle adjustment is			
	ABE-150	<ul style="list-style-type: none">convenient, easy to calibrate			
	ABE-200	<ul style="list-style-type: none">◆ Artificial Intelligence recognition technology,digital conversion and superior signal filtering			
	ABE-250	<ul style="list-style-type: none">◆ With high levels of anti-RFI/EMI capability◆ Unique design of the digital filter circuit			
	ABH-50L	<ul style="list-style-type: none">◆ Passed CE,FCC,ROHS,IP55 certification◆ 4 beams active infrared detector	<ul style="list-style-type: none">◆ Working voltage:DC12 ~ 24V◆ Response speed:50~700msec◆ Temperature: -25 ℃ ~ +55 ℃◆ Relative humidity: 5% ~ 95%◆ Horizontal angle adjustment:180 °?90 °◆ Vertical angle adjustment:°10 °◆ Material:PC◆ Size:370*100*100mm◆ Packing:9PCS/Carton	\$35.00	\$33.00
	ABH-100L	<ul style="list-style-type: none">◆ High-power transmitter,sensitivity surplus degree up to 90%			
	ABH-150L	<ul style="list-style-type: none">◆ Anti-lightning circuit design◆ With rain cover design,C relay output			
	ABH-200L	<ul style="list-style-type: none">◆ Adjustable of beam interdiction period,to make it more flexible and			
	ABH-250L	<ul style="list-style-type: none">adaptable◆ Professional anti-jamming optical housing◆ High-power infrared receiver tube,low-power process technology			
	AI-02(5,10)			\$12.00	\$11.50
	AI-02(20,30)	<ul style="list-style-type: none">◆ Passed CE,FCC,ROHS,IP55 certification	<ul style="list-style-type: none">◆ Model:AI-2 AI-4 AI-6	\$15.00	\$14.50
	AI-02(40,60)	<ul style="list-style-type: none">◆ Can be installed at door>window>passage etc	<ul style="list-style-type: none">◆ Total machine length(cm):36 70 120	\$16.00	\$15.50
	AI-04(5,10)	<ul style="list-style-type: none">◆ Aptitude judgement,prevent traditionally false alarm	<ul style="list-style-type: none">◆ Alarm distance(m):5 to 60	\$18.00	\$17.50
	AI-04(20,30)	<ul style="list-style-type: none">◆ Recognize object,can distinguish size of traversing object,will not alarm when the intruder is a cat or a dog	<ul style="list-style-type: none">◆ Power: DC12 ~ 18V	\$20.00	\$19.50
	AI-04(40,60)		<ul style="list-style-type: none">◆ Touch off time:40ms	\$23.00	\$22.50
	AI-06(5,10)	<ul style="list-style-type: none">◆ Anti-cutting function disturbs technology	<ul style="list-style-type: none">◆ Alarm time≥1.5sec	\$27.00	\$26.50
	AI-06(20,30)	<ul style="list-style-type: none">◆ Anti-rain function can be used outdoor of wet places	<ul style="list-style-type: none">◆ Horizontal angle adjustment:180 °?90 °	\$28.00	\$27.00
	AI-06(40,60)	<ul style="list-style-type: none">◆ Install and debug easily	<ul style="list-style-type: none">◆ Environment temperature:-25℃ ~ +55℃◆ Comparative humidity:≤95%	\$31.00	\$30.50






Photo	Model	Main Features	Specification	Unit Price (USD)	
				10-50 PCS	More than 50 PCS
GSM/PSTN Alarm Control Panel					
	AI-GSM01 (GSM&PSTN panel)	<ul style="list-style-type: none">◆ 255 wireless zone,8 wired zone◆ PSTN(land line)& GSM dual-network alarm system◆ LCD display,convenient to operate by keyboard◆ Automatically dial the stored phone numbers and send SMS while alarming◆ One output port to control the external electrical device,such as video camera,light,etc◆ Can connect with alarming monitoring center	<ul style="list-style-type: none">◆ Working voltage:DC12V◆ Frequency:315MHZ or 433MHZGSM frequency:900/1800MHZ or 850/1900MHZ◆ Remote control distance: > 100m(open area)◆ Detector emitting distance:100m◆ PIR detection distance:9-12m	\$105.00	\$103.00
	AI-GSM02 (GSM panel)	<ul style="list-style-type: none">◆ 8 wireless alarm zones,2 NC wired zones,1 wireless emergency calling,1 wireless fire alarm zone◆ Adopting WAVECOM GSM dual-band module◆ Intergrated color LCD display and keyboard settings◆ While alarming,host will send SMS message to 3 groups of mibile phones,and automatically dial 3 groups of phone numbers◆ Can connect with alarming monitoring center	<ul style="list-style-type: none">◆ Frequency:315MHZ or 433MHZ◆ GSM frequency:900/1800MHZ or 850/1900MHZ◆ Alarm response time: 8seconds◆ Alarm noise: 110db◆ Working environment:-10℃ ~ +55℃◆ Humidity: 95% no condensation	\$90.00	\$88.00
	AI-GSM05 (GSM panel) 850/900/1800/ 1900MHZ	<ul style="list-style-type: none">◆ 7 wired zones and 99 wireless zones◆ Up to code 8 wireless remote control◆ LCD display, built-in clock, easy and intuitive◆ Full voice guide, easy to operate.◆ Built-in intercom speaker, support external speaker◆ Timing arm and disarm: 3 groups of timing arming, 3 groups of timing disarm.◆ Preset 6 groups of alarm phone automatically dials the telephone voice alarm host.◆ Preset 3 groups SMS phone, send SMS alarm host automatically.		US\$66.00	US\$64.00
	AI-GSM06 (GSM&PSTN panel) 850/900/1800/ 1900MHZ	<ul style="list-style-type: none">◆ Includes 2 wired zones and 99 wireless zones.◆ With dual network of GSM + telephone cable, the System is more secure and reliable.◆ With the quad-band GSM module for global use.◆ Supports code pairing with 8 wireless remote controllers at the most.◆ LCD screen with a built-in clock.◆ With voice prompts for easy operations.◆ Supports 3 groups of timed arming and 3 groups of timed disarming.◆ The main device can dial alarm calls to 6 preset phone numbers and 3 groups of SMS.		US\$64.50	US\$63.50
	AI-GSM07 (GSM&PSTN panel) 850/900/1800/ 1900MHZ	<ul style="list-style-type: none">◆ 4 wired and 10 wireless zones, each can support 10 detectors (the maximum is 100).◆ Display in both Chinese and English language. The built-in clock is convenient for time checking.◆ Original operation system for the main unit allows simple operation.◆ Support card access control system, needless to carry the traditional remote control.◆ Code pairing for up to 8 wireless remote controls.◆ Built-in intercom speakers with high acoustic quality and large volume.◆ Preset 6 alarm phone numbers, which the main unit shall dial automatically to make voice alarm.◆ Preset 3 SMS numbers, to which the main unit shall send the alarm SMS automatically.		US\$81.00	US\$79.00

Photo	Model	Main Features	Specification	Unit Price (USD)	
				10-50 PCS	More than 50 PCS
	AI-GSM08 (GSM panel) 850/900/1800/ 1900MHZ	<ul style="list-style-type: none"> ◆ 4 wired and 10 wireless zones, each can support 10 detectors (the maximum is 100). ◆ Fashionable and high-tech touch keyboard ◆ Display in both Chinese and English language. The built-in clock is convenient for time checking. ◆ Original operation system for the main unit allows simple operation. ◆ Support card access control system, needless to carry the traditional remote control. ◆ Code pairing for up to 8 wireless remote controls. ◆ Built-in intercom speakers with high acoustic quality and large volume. ◆ Arm/disarm at regular time. ◆ Preset 6 alarm phone numbers, which the main unit shall dial automatically to make voice alarm. ◆ Preset 3 SMS numbers, to which the main unit shall send the alarm SMS automatically. 		US\$90.50	US\$88.50
	AI-TEL01 (PSTN panel)	<ul style="list-style-type: none"> ◆ It has 100 wireless zone ◆ 6 standard wired zone alarm, 2 standard outlet to control small appliance ◆ Automatic dialing 6 groups of telephone number which pre-setting ◆ With the function which can get the first line when alarm ◆ With international Contact ID alarm communication format 	<ul style="list-style-type: none"> ◆ Frequency: 315MHZ or 433MHZ ◆ GSM frequency: 900/1800MHZ or 850/1900MHZ ◆ Remote control distance: > 100m (open area) ◆ Detector emitting distance: > 500m (open area) ◆ PIR detection distance: 9-12m 	\$65.00	\$63.00
	AI-TEL02 (PSTN panel)	<ul style="list-style-type: none"> ◆ 8 wireless zones, 6 wired zones, and 1 output for alarm center ◆ Dial 6 groups of phone number automatically ◆ Advanced learning code function ◆ With super password, project password, and user password three grades for the using rights management ◆ With international Contact ID alarm communication format 	<ul style="list-style-type: none"> ◆ Working voltage: AC220V or DC9.6V ◆ Alarm current: < 10mA ◆ Alarm noise: < 100db ◆ Working environment: -10°C ~ +55°C ◆ Humidity: 95% no condensation 	\$52.00	\$50.00
Wired Alarm Control Panel					
	AI-728	<ul style="list-style-type: none"> ◆ High-speed communication format: 12 format contain Ademco Contact ID (report all the codes), Ademco Contact ID (Programmable code), 4+2, Personal Communication etc. 	<ul style="list-style-type: none"> ◆ Single-zone connection: (4+2) zone; double zone connection: (8+2) zone ◆ Dimension: 140*99.8*1.6 mm 	\$22.00	\$20.50
	AI-728EX	<ul style="list-style-type: none"> ◆ Battery Charger: 350mA (AI-728ULT), 360mA (AI-728/728EX) with battery tester ◆ AUX power output: 450mA (AI-728ULT), 400mA (AI-728/728EX) 	<ul style="list-style-type: none"> ◆ (4+2) zone ◆ Dimension: 140*99.8*1.6 mm 	\$22.00	\$20.50
	AI-728ULT	<ul style="list-style-type: none"> ◆ Bell Output: 1A, with automatic reset electronic fuse, limiting 3A ◆ Metal case and with transformer to be sold separately 	<ul style="list-style-type: none"> ◆ Single-zone connection: (4+2) zone; double zone connection: (8+2) zone ◆ Dimension: 140*72.6*1.6 mm 	\$22.00	\$20.50
	AI-738	<ul style="list-style-type: none"> ◆ Maximun 5 keypads can be connected ◆ Telephone line monitoring ◆ 256 event memory 	<ul style="list-style-type: none"> ◆ Single-zone connection: (6+2) zone; double zone connection: (12+2) zone ◆ Dimension: 190*86*1.6mm 	\$23.00	\$16.00
	AI-738EX	<ul style="list-style-type: none"> ◆ Every defence area with anti-tamper trigger display automatically ◆ Battery Charger: 350mA (AI-738ULT), 360mA (AI-738/738EX) with battery tester 	<ul style="list-style-type: none"> ◆ (7+2) zone; ◆ Dimension: 190*86*1.6mm 	\$35.00	\$28.00








Photo	Model	Main Features	Specification	Unit Price (USD)	
				10-50 PCS	More than 50 PCS
	AI-738ULT	<ul style="list-style-type: none"> ◆ AC power input: AC16.5V, 3A, 50-60HZ ◆ Metal case and with transformer to be sold separately 	<ul style="list-style-type: none"> ◆ Single-zone connection: (8+2) zone; double zone connection: (16+2) zone ◆ Dimension: 190*72.5*1.6mm 	\$40.00	\$35.00
	AI-748	<ul style="list-style-type: none"> ◆ Maximun 5 keypads can be connected ◆ Telephone line monitoring ◆ High-speed communication format ◆ Every defence area with anti-tamper trigger display automatically 	<ul style="list-style-type: none"> ◆ Single-zone connection: (12+2) zone; double zone connection: (24+0) zone ◆ Dimension: 190*101.5*1.6 mm 	\$50.00	\$40.00
	AI-748EX	<ul style="list-style-type: none"> ◆ Battery Charger: 360mA with battery tester ◆ AUX power output: 1000mA ◆ Bell Output: 1A ◆ AC power input: AC16.5V, 3A, 50-60HZ ◆ Metal case and with transformer to be sold separately 	<ul style="list-style-type: none"> ◆ (12+2) zone ◆ Dimension: 190*101.5*1.6 mm 	\$50.00	\$40.00
	AI-636	<ul style="list-style-type: none"> ◆ Built-in one zone input ◆ Adjustable brightness ◆ Can set four doorbell zone 	◆ Size: 143*78*23 mm	\$10.00	\$9.00
	AI-646	<ul style="list-style-type: none"> ◆ 3 groups of emergency alarm button ◆ Low power consumption (20mA) ◆ Defence zone fault monitoring ◆ Fireproof housing 	◆ Size: 135*97*32 mm	\$10.00	\$9.00
Passive Infrared Detector(not contain bracket)					
	AI-P85 (Outdoor detector with pet immunity) 100% waterproof and fireproof material	<ul style="list-style-type: none"> ◆ PIR intrusion detector integrating the most advanced security technology ◆ It adopts 2 dual PIR sensors with high accuracy, intelligent digi-tal chip, make an accurate judgment of true intruder or other interference that can cause wrong alarm ◆ And it is with function of automatic memory of environmental change ◆ Prevent effectively the interference caused by a 25 kg past or 10 cats, insect, mouse, birds etc. 	<ul style="list-style-type: none"> ◆ Working voltage: DC9-16V ◆ Working current: 30mA 12VDC ◆ Detection Range: 11.6m*11.6m ◆ Alarm output: NC.100mA/28VDC ◆ Installation height: 2m-2.7m ◆ Anti white light resistance: >20000LUX ◆ Anti -EMI/RFI: 10V/m(10MHz-1000MHz) ◆ Motion test: 0.2m/s-3.5m/s(0.6ft-11ft) ◆ Size: 176*85*69mm 	\$30.00	\$27.00
	AI-P301 (Curtain PIR detector)	<ul style="list-style-type: none"> ◆ Indoor curtain PIR detector ◆ Type of sensor: dual lower-noise infrared sensor ◆ Output alarm: NC/NO optional ◆ LED ON/OFF optional ◆ Adopt SMT design, enhance the ability of diamagnetic ◆ Alarm output: NC/NO optional Contact capacity: 28VDC, 100mA 	<ul style="list-style-type: none"> ◆ Working voltage: DC10V~16V ◆ Working current: 20mA (DC12V) ◆ Detection distance: 6m/11m optional ◆ Detection angle: 15 degree ◆ Mounting height: 1.8m~2.5m (suggest 2m) ◆ Size: 110mm*69mm*41mm 	\$8.30	\$8.00
	AI-P127 (Curtain PIR detector)	<ul style="list-style-type: none"> ◆ Indoor curtain PIR detector ◆ Type of sensor: dual low noise pyroelectric infrared sensor ◆ Auto temperature compensation ◆ Resisting white light strength >6500LUX ◆ Alarm output: NC/NO optional ◆ LED ON/OFF optional ◆ Mounting : wall mounted 	<ul style="list-style-type: none"> ◆ Working voltage: DC10V~16V ◆ Detection distance: 6m/11m optional ◆ Detection angle: 15 degree ◆ Mounting height: 1.8m~2.5m (suggest: 2m) ◆ Alarm output: NC/NO optional, contact capacity: 28VDC, 100mA ◆ Size: 94mm*49mm*35mm 	\$9.00	\$8.00






Photo	Model	Main Features	Specification	Unit Price (USD)	
				10-50 PCS	More than 50 PCS
	AI-P526 (Wide angle PIR detector)	<ul style="list-style-type: none"> ◆ Indoor wide angle PIR detector ◆ Type of sensor: dual low noise pyroelectric infrared sensor ◆ Anti white light strength>6500LUX ◆ Alarm output:NC/NO optional ◆ Pulse counting 1P/2P optional ◆ LED ON/OFF optional ◆ Mounting:wall mounted 	<ul style="list-style-type: none"> ◆ Working voltage:DC10V~16V ◆ Working current: 20mA (DC12V) ◆ Detection distance: 12m ◆ Detection angle: 100 degree ◆ Mounting height: suggest 2.2m ◆ Alarm output: NC/NO optional Contact capacity: 28VDC, 100mA ◆ Size: 90mm*62mm*44mm 	\$10.00	\$9.00
	AI-P55 (PIR detector)	<ul style="list-style-type: none"> ◆ New streamlined design ◆ Low noise, high sensitivity, anti-electromagnetic interference ◆ Fully protected and sealed optical lenses, anti-mosquito interference ◆ Easy installation with lock, ease of construction 	<ul style="list-style-type: none"> ◆ Detection distance:14m ◆ Working voltage:9-15VDC ◆ Working current:14mA ◆ Installation height:2.2m-3.0m ◆ Anti-white light interference 8000LUX ◆ Anti-EMI: 30V/M(10MHz-1000MHz) ◆ Alarm output:NC 	\$8.00	\$7.00
	AI-P476 (PIR detector)	<ul style="list-style-type: none"> ◆ Low noise,high sensitivity,dual source infrared sensor ◆ Ideal for residential,anti-theft ◆ Automatic temperature compensation ◆ Anti EMI:Metal shield RFI ◆ Lens:2nd generation Fresnel lens 	<ul style="list-style-type: none"> ◆ Working Voltage: 12VDC ◆ Detection distance: 11M ◆ Mounting height:2-2.7m ◆ Working environment temperature: -10 °C ~ +50 °C ◆ Relative humidity:5% ~ 95% RH ◆ Alarm output:NC, 28VDC 0.15A ◆ Size: 93 * 67 * 52mm 	\$7.00	\$6.00
	AI-P101 (PIR & Microwave detector)	<ul style="list-style-type: none"> ◆ Adopting doppler effect +energy analysis ◆ Microwave adopting X-Band plane antenna ◆ Auto temperature compensation function ◆ Anti white light strength>6500LUX ◆ LED ON/OFF optional ◆ Adopting SMT design,superhigh ability of diamagnetism ◆ LED indicating:green is infrared; yellow is microwave; red is alarm 	<ul style="list-style-type: none"> ◆ Working voltage:DC10V~16V(DC10V~24V optional) ◆ Detection distance: 12m ◆ Detection angle: 100 degree ◆ Mounting: wall mounted ◆ Mounting height: suggest 2.2m ◆ Alarm output: NC/NO optional; Contact capacity: 28VDC, 100mA ◆ Size:135mm*66mm*64mm 	\$15.00	\$14.00
	AI-P7225 (PIR & Microwave detector)	<ul style="list-style-type: none"> ◆ Indoor infrared with microwave detector ◆ With excellent capacity of anti-false alarm ◆ Simple and quick installation ◆ Built-in temperature compensation and microwave anti-interference function ◆ Durable ABS shell,excellent anti-shock function 	<ul style="list-style-type: none"> ◆ Operating voltage: 7.5~ 16VDC ◆ Detection distance:7.6m ◆ Microwave frequencies : 24.125GHZ ◆ Anti-tamper output:NC 50mA,24VDC ◆ Relative humidity: 5% ~ 95% RH ◆ Anti Anti-white light: 8000LUX ◆ Size: 119*71*42mm 	\$12.00	\$11.00
	AI-P75 (PIR with pet immunity)	<ul style="list-style-type: none"> ◆ Stable performance, greatly reduce the occurrence of false positives ◆ Two independent anti-polarity dual source infrared sensor ◆ Automatic temperature compensation ◆ Automatically adjust of pulses 	<ul style="list-style-type: none"> ◆ Detect distance: 11m ?11m ◆ Input power:11 to 16VDC ◆ Installation height:2m to 2.7m ◆ Environment temperature: -10 °C ~ +50 °C ◆ Alarm Output:NC28Vdc; 0.15A ◆ Size: 68?27?2mm 	\$16.00	\$15.00
	AI-P971 (Vibration sensor)	<ul style="list-style-type: none"> ◆ Photoelectric vibration sensor ◆ Sensitivity is adjustable ◆ Microprocessor design improves false alarm immunity ◆ Tamper immunity ◆ Alarm indication 	<ul style="list-style-type: none"> ◆ Operating voltage:9 to 16VDC ◆ Operating current:15mA ◆ Alarm contact:NC,12VDC,100mA max ◆ Tamper contact:NC,12VDC,100mA max ◆ Dimension:26*85*24mm 	\$7.50	\$6.80

Photo	Model	Main Features	Specification	Unit Price (USD)	
				10-50 PCS	More than 50 PCS
	AI-P456 (Glass-break detector)	<ul style="list-style-type: none"> ◆ Software driven, 8/12 bit microprocessor-controlled digital signal processing ◆ High frequency sound pressure detection ◆ Full audio spectrum 7 frequency signal and impact analysis including infra-sound pressure analysis ◆ Unique acoustic microphone chamber and casing design 	<ul style="list-style-type: none"> ◆ Detection distance: 9m ◆ Working voltage :9-16VDC ◆ Working current: 18mA ◆ Working temperature: -10 °C ~ +50 °C ◆ Alarm output: NC 28VDC 0.15A ◆ Size: 90x66x25mm 	\$8.00	\$7.50
	AI-P465 (Ceiling detector)	<ul style="list-style-type: none"> ◆ Low noise, high sensitivity, dual source infrared sensor ◆ Suitable for ceiling mount, ideal for residential security use ◆ Secondary automatically adjust the number of pulses ◆ Automatic temperature compensation; ◆ Flame-retardant shell ◆ Anti EMI: metal shield RFI 	<ul style="list-style-type: none"> ◆ Input power: 9—16VDC, 18mA ◆ Alarm display: red LED, constant light for 3 seconds ◆ Lens: Fresnel lens ◆ Detection Range: 7.5m*6m (Installation height 2.4m) ◆ Alarm output: NC.150mA/28VDC ◆ Operating temperature: -10 °C ~ +50 °C ◆ Size: Φ108*5mm 	\$8.00	\$7.50
	AI-C120	<ul style="list-style-type: none"> ◆ PC materials, environmental economy, high temperature, corrosion-resistant ◆ Easy to install, practical ◆ Multi-angle adjustable detection range of the detector is more accurate ◆ Suitable for all wall-detector 		\$1.00	\$0.90
	AI-C121	<ul style="list-style-type: none"> ◆ Specialized 86 box bracket 	<ul style="list-style-type: none"> ◆ Can use together with AI-P127, AI-P526, AI-P101 	\$1.50	\$1.30
Independent Carbon Monoxide Detector					
	AI-CO21	<ul style="list-style-type: none"> ◆ Standby current: <15μA ◆ Alarm current: <30mA ◆ Operating temperature: -10 °C to +50 °C ◆ Operating Humidity: 95% RH 	◆ Power supply: DC 9V battery	\$12.00	\$11.00
	AI-CO22	<ul style="list-style-type: none"> ◆ Detection area: 20 m2 ◆ SPL: 85 dB / 3m (10ft) ◆ Size: Φ106* 53MM 	◆ Power supply: AC110-265V, 9V back-up battery	\$12.00	\$11.00
	AI-CO31	<ul style="list-style-type: none"> ◆ Standby current: <15μA ◆ Alarm current: <30mA ◆ Operating temperature: -10 °C to +50 °C ◆ Operating Humidity: 95% RH 	◆ Power supply: DC 9V battery	\$11.00	\$10.00
	AI-CO32	<ul style="list-style-type: none"> ◆ Detection area: 20 m2 ◆ SPL: 85 dB / 3m (10ft) ◆ Size: Φ107* 36MM 	◆ Power supply: AC110-265V, 9V back-up battery	\$12.00	\$11.00
Smoke Detector					
	AI-S021 (Independent type)	<ul style="list-style-type: none"> ◆ Standby current: <15μA ◆ Alarm current: <30mA ◆ Operating temperature: -10 °C to +50 °C ◆ Operating Humidity: 95% RH 	◆ Operating voltage: DC9V battery	US\$9.00	US\$8.00
	AI-S022 (Independent type)	<ul style="list-style-type: none"> ◆ Detection area: 20 m2 ◆ Sensitivity: 2.06% ft ◆ SPL: 85 dB / 3m (10ft) ◆ Size: Φ106* 53MM 	◆ Power supply: AC110-265V, 9V back-up battery	US\$9.00	US\$8.00














Photo	Model	Main Features	Specification	Unit Price (USD)	
				10-50 PCS	More than 50 PCS
	AI-S031 (Independent type)	<ul style="list-style-type: none"> ◆ Dedicated chip signal processing, and more energy efficient, more stable ◆ Alarm output: sound and light alarm ◆ Infrared photoelectric sensor ◆ Anti-electromagnetic interference ◆ Be able to adapt to changes in the environment ◆ Dust and pest proof, anti-white light interference 	<ul style="list-style-type: none"> ◆ Operating voltage: DC 9V battery ◆ Standby current: <15μA ◆ Alarm current: <30mA ◆ Operating Humidity: 95% RH ◆ Detection area: 20 m² ◆ Sensitivity: 2.06% ft ◆ SPL: 85 dB / 3m (10ft) ◆ Size: Φ107 * 36MM 	\$9.00	\$8.00
	AI-S041 (Wired networking type)	<ul style="list-style-type: none"> ◆ Power interrupt reset / automatic reset optional ◆ Non-polarity power input ◆ Alarm indication: red LED on ◆ Alarm output NO / NC optional ◆ SMT technology, strong stability ◆ Metallic shield, good anti-interference (20V/m-1GHz) 	<ul style="list-style-type: none"> ◆ Operating voltage: DC 12-30V ◆ Operating temperature: -10℃ to +50℃ ◆ Operating Humidity: 95% RH ◆ Detection area: 80 m² ◆ Size: Φ103*53mm (with base) 	\$11.00	\$10.00
Gas Leakage Detector					
	AI-G011 (Wired networking type)	<ul style="list-style-type: none"> ◆ Alarm output: relay output + sound and light alarm+electromagnetic pulse output ◆ Adopt micro-processing and SMT technology, good stability ◆ MAIunction auto-check indicator ◆ Executive standard: GB15322; EN50194; UL1484 	<ul style="list-style-type: none"> ◆ Operating voltage: AC 220V ◆ Alarm current: <120mA ◆ Gas species: LPG and natural gas ◆ Alarm level: 10% ?5% LEL ◆ Equipped with accessories: electromagnetic valve or manipulator ◆ Size: 115 * 73 * 46 mm 	\$13.00	\$12.00
	AI-G012 (Wired networking type)	<ul style="list-style-type: none"> ◆ Alarm output: relay output + sound and light alarm+electromagnetic pulse output ◆ Adopt micro-processing and SMT technology, good stability ◆ MAIunction auto-check indicator ◆ Executive standard: GB15322; EN50194; UL1484 	<ul style="list-style-type: none"> ◆ Operating voltage: DC12-24V ◆ Alarm current: <120mA ◆ Gas species: LPG and natural gas ◆ Alarm level: 10% ?5% LEL ◆ Equipped with accessories: electromagnetic valve or manipulator ◆ Size: 115 * 73 * 46 mm 	\$13.00	\$12.00
	AI-G013 (Independent type)	<ul style="list-style-type: none"> ◆ Alarm output: relay output + sound and light alarm+electromagnetic pulse output ◆ Adopt micro-processing and SMT technology, good stability ◆ MAIunction auto-check indicator ◆ Executive standard: GB15322; EN50194; UL1484 	<ul style="list-style-type: none"> ◆ Operating voltage: AC 220V ◆ Standby current: <70mA ◆ Gas species: LPG and natural gas ◆ Alarm level: 10% ?5% LEL ◆ Equipped with accessories: electromagnetic valve or manipulator ◆ Size: 115 * 73 * 46 mm 	\$13.00	\$12.00
	AI-G031 (Wired networking type)	<ul style="list-style-type: none"> ◆ Installation way: ceiling mounted ◆ Alarm output: relay output + sound and light alarm+electromagnetic pulse output ◆ Adopt micro-processing and SMT technology, good stability ◆ Executive standard: GB15322; EN50194; UL1484 	<ul style="list-style-type: none"> ◆ Operating voltage: AC 220V ◆ Alarm current: <120mA ◆ Gas species: LPG and natural gas ◆ Alarm level: 10% ?5% LEL ◆ Equipped with accessories: electromagnetic valve or manipulator ◆ Size: Φ116*44 mm 	\$13.00	\$12.00
	AI-G033 (Wired type)	<ul style="list-style-type: none"> ◆ Wired gas leakage detector ◆ Ceiling mounted ◆ Relay output alarm ◆ High Reliability sensor ◆ MCU processing adopted, SMT adopted, good stability ◆ MAIunction auto-check indicator 	<ul style="list-style-type: none"> ◆ Operating voltage: DC12-24V ◆ Alarm level: 10% ?% LEL ◆ Alarm output: Sound&Flash ◆ Execute criterion: GB15322; EN50194; UL1484 ◆ Dimension: Φ104*51mm 	\$11.00	\$10.00

Photo	Model	Main Features	Specification	Unit Price (USD)	
				10-50 PCS	More than 50 PCS
Alarm Accessories we also can provide with best price					
	ES-626 (Siren)	◆Independent high tone horn design,large alarm volume ◆Beautiful appearance,loud voice,suitable for installation in corridors,windows and other places.	◆Rated voltage: DC12V ◆Working voltage:9~13VDC ◆Working current:280~480mA ◆Rated Power:15W ◆Sound pressure: 110?DB ◆Size:106*100*110mm (with bracket)	\$4.00	\$3.50
	103 (Indoor siren with strobe)	◆Streamlined design,with decorative ◆Common red lights setting,strong deterrence ◆ABS case,with certain fire-retardant properties ◆Variety of installation options,flexible and convenient	◆Rated voltage: DC12V ◆Working voltage:9~13VDC ◆Working current:150~250mA ◆Flashing frequency:150 beats / min ◆Sound pressure: 110?DB ◆Size:122.5 * 73.5 * 47.5mm	\$3.00	\$2.50
	LM-107 (Outdoor siren with strobe)		◆Housing material:PC/white ◆Operating voltage:6-18VDC ◆Related voltage:12VDC ◆Rated current:300mA ◆SPL Db/1M:115 ◆Without battery ◆Size:210*130*78mm	\$8.00	\$7.00
	LM-106 (Outdoor siren with strobe)		◆Power supply voltage:13.8 to 14.2VDC ◆UV prevention,Metal cover inside ◆Flash rate:120 times/minute ◆SPL:120db/m ◆Sound type:single tone ◆Without battery ◆Size:270L*193W*100Hmm	\$20.00	\$19.00
	LM-105 (Strobe)		◆Rated current:100mA ◆Rated voltage:12VDC ◆Stroboscopic number ◆Size:450*290*375mm	\$3.50	\$3.20
	AI-EB01	◆Emergency button and exit button ◆ABS Housing ◆Alarm Output:NO and NC Output ◆Color: white	◆Voltage: 12 or 24V DC ◆Carrying current: 0.3A ◆Size: 76 *17* 17mm ◆Package:1set/PE bag,10sets/bag, 700sets/carton	\$1.00	\$0.80
	AI-EB02	◆Panic Button with Key ,emergency button ◆Color:White ◆ABS Housing ◆Output: NO and NC	◆Voltage:12 or 24V DC ◆Carrying current: 0.3A ◆Size: 86 x 86 x 32mm	\$1.20	\$1.00
	AI-EB03		◆Working voltage:12/24VDC ◆Power:10W ◆Switch state:NC/NO(single or dual) ◆Size:87mm*87mm*51mm	\$4.00	\$3.50
	AI-MC01 (Surface mount)	◆Excellent surface magnetic contact ◆Housing:fireproof ABS ◆Colour:white	◆Gap:13-19mm ◆Output:N.C. N.O. & changeover available ◆Size: 64*19*12.8mm ◆Packing:10SETS/PE bag	\$3.00	\$2.50
	AI-MC02 (Surface mount)	◆Excellent surface magnetic contact ◆Housing:fireproof ABS ◆Colour:white	◆Gap:15-25mm ◆Output:N.C ◆Size: 50*14*12mm ◆Packing:10SETS/PE bag	\$1.50	\$1.30

Photo	Model	Main Features	Specification	Unit Price (USD)	
				10-50 PCS	More than 50 PCS
	AI-MC07 (Surface mount)	<ul style="list-style-type: none"> ◆ Surface mounted magnetic contact ◆ ABS housing, ideal for wooden door or window ◆ Output: N.C. N.O. & changeover available 	<ul style="list-style-type: none"> ◆ Gap: 15-25mm available on request ◆ Dimension: 64*19*13mm ◆ Packing: 10SETS/PE bag 	\$0.82	\$0.62
	AI-MC03 (Recessed)	<ul style="list-style-type: none"> ◆ Excellent recessed magnetic contact ◆ Housing: ABS, white ◆ Output: N.C 	<ul style="list-style-type: none"> ◆ Gap: 15-25mm available on request ◆ Size: Φ10*18.5mm ◆ Packing: 20SETS/PE bag 	\$0.80	\$0.60
	AI-MC10 (Recessed)	<ul style="list-style-type: none"> ◆ Excellent Recessed Magnetic Contact ◆ Contact: N.C. N.O. & changeover available ◆ Housing: ABS ◆ Colour: white /brown 	<ul style="list-style-type: none"> ◆ Gap: 20-30mm ◆ Dimension: Φ19*25mm ◆ Packing: 10SETS/PE bag 	\$2.00	\$1.80
	AI-MC21 (Iron magnetic)	<ul style="list-style-type: none"> ◆ Housing: Alloy-Zn, grey ◆ Output: NC, NO or Changeover available ◆ Leads: 1007UL22AWG530mm, wire with cable available 	<ul style="list-style-type: none"> ◆ Gap: 40-60mm, 50-60mm available ◆ Dimension: 106*16*16mm 	\$5.00	\$4.80
	AI-MC04 (Roller shutter)	<ul style="list-style-type: none"> ◆ Roller shutter magnetic contact ◆ Contact switch: N.C. N.O. & changeover available ◆ Housing: Metal (Alloy-Al), grey 	<ul style="list-style-type: none"> ◆ Gap: 50 to 70mm ◆ Remarks: 4 screws included ◆ Packing: 1sets/bag 	\$5.00	\$4.80
	AI-MC25 (Roller shutter)	<ul style="list-style-type: none"> ◆ Magnetic contact for Metal door /rolling door ◆ Contact switch: N.C. N.O. & changeover available ◆ Metal case (alloy zinc), surface mounted type ◆ Inner packing: 1sets/bag 	<ul style="list-style-type: none"> ◆ Operating distance: 50 to 70mm ◆ Power: 10W ◆ Voltage: 100V ◆ Current: 0.5A 	\$7.00	\$6.50

Basic Terms:

- Above price shipping charge excluded
- T/T or Western Union or Paypal in advance.
- Warranty 1 year, all shipping charge at resellers' side
- Refund guaranteed with resellers pay shipping charge
- Above price subject to change upon market situation
- Built-in lithium batteries may NOT be shipped due to security control of couriers.
- Regular batteries for sensors and remotes will NOT be shipped unless arranged otherwise at extra cost
- Any information please contact Dennis Chan at dennis@security-warehouse.com for clarification