

















THE PRICELIST

Chinese Leading Alarm Products Manufacturer

Photo	Item No.	Main Features	Specification	EXW(USD)	
				1-200PCS	Alve 200PCS
Active Infrared Beam Detector					
	AI-20L	◆ Passed CE,FCC,ROHS,IP55 certification ◆ Can be used with access control system,used for wall,passage etc. ◆ Fully sealed design,rain-proof(fog),dust-proof(worm) ◆ With high levels of anti-RFI/EMI capability ◆ Professional anti-jamming optical housing	◆ Detecting distance:15m ◆ Working voltage: DC12~24V ◆ Operating temperature:-25℃ ~+55℃ ◆ Size:49.2*76*21.6mm ◆ Packing:200PCS/Carton	\$5.00	\$4.50
	AI-10F (Frequency adjustment single beam sensor)	◆ Passed CE,FCC,ROHS,IP55 certification ◆ Fully sealed design,rain-proof(fog),dust-proof(worm) ◆ With high levels of anti-RFI/EMI capability ◆ Professional anti-jamming optical housing	◆ Detecting distance:15m ◆ Working voltage: DC9~16V ◆ Switch Output: 1A Max, 25V ◆ Operating temperature:-25℃ ~+55℃ ◆ Size:69.5*26.4*22.5mm	\$5.00	\$4.50
	AI-5L (Retroreflective infrared detector)	◆ Apply to the alert of room near the entrance,exit>window,passage,stairs ◆ Transmitter and receiver integration design,adopt lens reflex way alert, simplify complex wiring work ◆ Detector adopt thin design,thickness only 23.3mm,wall installation,elegant appearance ◆ Material:ABS(white)	◆ Deteting distance:≤5m ◆ Light source: Infrared LED ◆ Response time:≥50ms ◆ Alarm signal:dry contact relay output contact capacity 30VAC/DC 0.5A ◆ Working voltage:11-28VDC ◆ Power:30mA(12V DC) ◆ Operating temperature:-20℃ ~+50℃	\$26.00	\$25.00
	AI-1D (Diffused Infrared Single Beam)	◆ Apply to the alert of room near the entrance,exit>window,passage,stairs ◆ Transmitter and receiver integration design, adopt lens reflex way alert, simplify complex wiring work ◆ Detector adopt thin design,thickness only 23.3mm,wall installation,elegant appearance ◆ Material:ABS(white)	◆ Indoor Deteting distance:0.1m-1m ◆ Light source: Infrared LED ◆ Response time:≥50ms ◆ Alarm signal:dry contact relay output ◆ contact capacity 30V AC/DC 0.5A ◆ Working voltage:11-24V DC ◆ Power:30mA(12V DC) ◆ Operating temperature:-20℃ ~+50℃ ◆ Weight: 80g	\$28	\$27
	ABT-20	◆ Passed CE,FCC,ROHS,IP55 certification ◆ 2 beams active infrared detector ◆ Used for wall,passage etc. ◆ Anti-glare up to 50,000 LUX, built-in automatic adjustment strong light filtering system ◆ Up and down optical lens can adjust the mechanical design,making adjustments more faster,convenient and accurate.	◆ Working voltage:DC12~24V ◆ Response speed:50~700msec ◆ Alarm output:Relay contact output NO or NC;Contact capacity DC30V 0.5Amax ◆ Operating temperature:-25℃ ~+55℃ ◆ Horizontal angle adjustment:180 °(± 90 °) ◆ Vertical angle adjustment:±10 ° ◆ Size:171*82*77mm ◆ Packing:20PCS/ Carton	\$10.50	\$10.00
	ABT-30				
	ABT-60				
	ABT-80				
	ABT-100				
	ABT-30S	◆ Fully sealed design,rain-proof(fog),dust-proof(worm) ◆ With high levels of anti-RFI/EMI capability ◆ Professional anti-jamming optical housing ◆ Case Material: PC	◆ Alert Distance: < 150m ◆ Induction Speed: 50-700ms ◆ Alarm Output: NC/NO; contact rating: AV/DC 30V/0.5mA ◆ Working Voltage: DC 12-24V; AC 11-18V ◆ Working Current: <100mA ◆ Tamper Output: NC; contact rating: AC/DC 24V/0.5mA ◆ Horizontal Angle Adjustment: 180°±90° ◆ Vertical Angle Adjustment: ±10°	\$25.00	\$24.00
	ABT-60S			\$26.00	\$25.00
	ABT-100S			\$27.00	\$26.00
	ABT-30F	◆ 4 channel of frequency adjustment active infrared double beam ◆ Can be used with access control system,extensive used ◆ Fully sealed design,rain-proof(fog),dust-proof(worm) ◆ With high levels of anti-RFI/EMI capability ◆ Professional anti-jamming optical housing	◆ Alert Distance: < 150m ◆ Induction Speed: 50-700ms ◆ Alarm Output: NC/NO; contact rating: AV/DC 30V/0.5mA ◆ Ganged Alarm: Yes ◆ Working Voltage: DC 12-24V; AC 11-18V ◆ Working Current: <100mA ◆ Tamper Output: NC; contact rating: AC/DC 24V/0.5mA ◆ Horizontal Angle Adjustment: 180°±90° ◆ Vertical Angle Adjustment: ±10°	\$26.00	\$25.00
	ABT-60F			\$28.00	\$26.00
	ABT-100F			\$30.00	\$28.00
	AI-F430		◆ Beam 2 ◆ Outdoor Alert Distance: < 120m ◆ Indoor Alert Distance: < 360m	\$30.00	US\$29.00









	AI-F460	<ul style="list-style-type: none"> ◆ 4 channel of FM active infrared double beam ◆ Can be used with access control system,extensive used 	<ul style="list-style-type: none"> ◆ Light Source Infrared digital pulse type ◆ Induction Speed ≤60ms ◆ Alarm Output NC& NO contact rating: AV/DC 30V/0.5mA ◆ Working Voltage 11V~28VDC ◆ Working Current ≤60mA ◆ Tamper Output NC contact rating: AC/DC 24V/0.5mA ◆ Horizontal Angle Adjustment 180° (±90°) ◆ Vertical Angle Adjustment ±10° ◆ Case Material PC from Germany 	\$32.00	US\$31.00
	AI-F4100	<ul style="list-style-type: none"> ◆ Fully sealed design,rain-proof(fog),dust-proof(worm) ◆ With high levels of anti-RFI/EMI capability ◆ Professional anti-jamming optical housing 		\$33.00	US\$32.00
	AI-F4120			\$35.00	US\$34.00
	AI-F430S		<ul style="list-style-type: none"> ◆ Beam 2 ◆ Outdoor Alert Distance: < 120m ◆ Indoor Alert Distance: < 360m ◆ Light Source Infrared digital pulse type ◆ Induction Speed ≤60ms ◆ Alarm Output NC& NO contact rating: AV/DC 30V/0.5mA ◆ Working Voltage 11V~28VDC ◆ Working Current ≤60mA ◆ Working Temperature -25℃~+55℃ ◆ Working Humidity 5%~95% (RH) ◆ Tamper Output NC contact rating: AC/DC 24V/0.5mA ◆ Horizontal Angle Adjustment 180° (±90°) ◆ Vertical Angle Adjustment ±10° ◆ Case Material PC from Germany 	\$30.00	US\$29.00
	AI-F460S	<ul style="list-style-type: none"> ◆ 4 channel of FM reflective lens active infrared double beam ◆ Can be used with access control system,extensive used ◆ Fully sealed design,rain-proof(fog),dust-proof(worm) ◆ With high levels of anti-RFI/EMI capability ◆ Professional anti-jamming optical housing 		\$31.00	US\$30.00
	AI-F4100S			\$33.00	US\$32.00
	AI-F4120S			\$34.00	US\$33.00
	AI-F830		<ul style="list-style-type: none"> ◆ Beam 2 ◆ Outdoor Alert Distance: < 120m ◆ Indoor Alert Distance: < 360m ◆ Light Source Infrared digital pulse type ◆ Induction Speed ≤60ms ◆ Alarm Output NC& NO contact rating: AV/DC 30V/0.5mA ◆ Working Voltage 11V~28VDC ◆ Working Current ≤60mA ◆ Working Temperature -25℃~+55℃ ◆ Working Humidity 5%~95% (RH) ◆ Tamper Output NC contact rating: AC/DC 24V/0.5mA ◆ Horizontal Angle Adjustment 180° (±90°) ◆ Vertical Angle Adjustment ±10° ◆ Case Material PC from Germany 	\$35.00	US\$33.00
	AI-F860	<ul style="list-style-type: none"> ◆ 8 channel of FM active infrared double beam ◆ Can be used with access control system,extensive used ◆ Fully sealed design,rain-proof(fog),dust-proof(worm) ◆ With high levels of anti-RFI/EMI capability ◆ Professional anti-jamming optical housing 		\$36.00	US\$34.00
	AI-F8100			\$38.00	US\$36.00
	AI-F8120			\$40.00	US\$38.00
	ABT-M10 (Active Infrared Double Beam)	<ul style="list-style-type: none"> ◆ Apply to the alert of room near the entrance,exit>window,passage,stairs ◆ Transmitter and receiver integration design, adopt lens reflex way alert, simplify complex wiring work ◆ Detector adopt thin design,thickness only 23.3mm,wall installation,elegant appearance ◆ Mounting: Wall mounted ◆ Wiring Terminal Blocks ◆ Alarm Indication: Red LED indication ◆ Material:ABS(white) 	<ul style="list-style-type: none"> ◆ Number Of Beams: 2 ◆ Indoor Detection Distance:10 m ◆ Working Voltage: DC11-24V (nonpolarity) ◆ Max Current: 40mA(DC12V) ◆ Response Time: 100m sec ◆ Alarm Output: NC/NO ◆ Contact Capacity: 30V AC/DC 0.5A max ◆ Working Temperature: -10℃ to +50℃ ◆ Color: Creamy-white ◆ Dimensions: 106*62*25mm ◆ Weight: 150g 	\$20.00	\$18.00
	ABE-50(NEW)	<ul style="list-style-type: none"> ◆ Passed CE,FCC,ROHS,IP55 certification 	<ul style="list-style-type: none"> ◆ Working voltage:DC12 ~ 24V ◆ Operating temperature: -25℃ ~ +55℃ ◆ Relative humidity: 5% ~ 95% (RH) ◆ Tamper output:contact output NC; Contact rating:DC24V 0.5Amax ◆ Horizontal angle adjustment:180°(± 90°) ◆ Vertical angle adjustment:±10° ◆ Material:PC ◆ Size:240*88*85mm ◆ Packing:12PCS/Carton 	\$20.00	\$18.00
	ABE-100(NEW)	<ul style="list-style-type: none"> ◆ New 3 beams active infrared detector ◆ Used for wall,passage etc. 			
	ABE-150(NEW)	<ul style="list-style-type: none"> ◆ Ten signal design, horizontal/vertical optical angle adjustment is convenient, easy to calibrate 			
	ABE-200(NEW)	<ul style="list-style-type: none"> ◆ With high levels of anti-RFI/EMI capability 			
	ABE-250(NEW)	<ul style="list-style-type: none"> ◆ Unique design of the digital filter circuit 			
	ABE-50	<ul style="list-style-type: none"> ◆ Passed CE,FCC,ROHS,IP55 certification 	<ul style="list-style-type: none"> ◆ Working voltage:DC12 ~ 24V ◆ Operating temperature: -25℃ ~ +55℃ ◆ Relative humidity: 5% ~ 95% (RH) ◆ Tamper output:contact output NC; Contact rating:DC24V 0.5Amax ◆ Horizontal angle adjustment:180°(± 90°) ◆ Vertical angle adjustment:±10° ◆ Material:PC ◆ Size:240*88*85mm ◆ Packing:12PCS/Carton 	\$22.00	\$21.50
	ABE-100	<ul style="list-style-type: none"> ◆ New 3 beams active infrared detector ◆ Used for wall,passage etc. 			
	ABE-150	<ul style="list-style-type: none"> ◆ Ten signal design, horizontal/vertical optical angle adjustment is convenient,easy to calibrate 			
	ABE-200	<ul style="list-style-type: none"> ◆ Artificial Intelligence recognition technology,digital conversion and superior signal filtering 			
	ABE-250	<ul style="list-style-type: none"> ◆ With high levels of anti-RFI/EMI capability 			
	ABH-50L	<ul style="list-style-type: none"> ◆ Passed CE,FCC,ROHS,IP55 certification ◆ 4 beams active infrared detector 	<ul style="list-style-type: none"> ◆ Working voltage:DC12 ~ 24V ◆ Response speed:50~700msec ◆ Temperature: -25℃ ~ +55℃ ◆ Relative humidity: 5% ~ 95% 		
	ABH-100L	<ul style="list-style-type: none"> ◆ High-power transmitter,sensitivity surplus degree up to 90% ◆ Anti lightning circuit design 			












	ABH-150L	<ul style="list-style-type: none"> ◆Anti-lightning circuit design ◆With rain cover design,C relay output 	<ul style="list-style-type: none"> ◆Relative humidity: 5% ~ 95% ◆Horizontal angle adjustment:180 °(± 90 °) ◆Vertical angle adjustment:± 10 ° ◆Material:PC ◆Size:370*100*100mm ◆Packing:9PCS/Carton 	\$30.00	\$29.00
	ABH-200L	<ul style="list-style-type: none"> ◆Adjustable beam interdiction period,to make it more flexible and adaptable 			
	ABH-250L	<ul style="list-style-type: none"> ◆Professional anti-jamming optical housing ◆High-power infrared receiver tube,low-power process technology 			
	ABH-250L				
	AI-02(5,10)	<ul style="list-style-type: none"> ◆Passed CE,FCC,ROHS,IP55 certification 	<ul style="list-style-type: none"> ◆Model:AI-2 AI-4 AI-6 ◆Total machine length(cm):36 70 120 ◆Alarm distance(m):5 to 60 ◆Power: DC12 ~ 18V ◆Touch off time:40ms ◆Alarm time≥1.5sec ◆Horizontal angle adjustment:180 ° (± 90 °) ◆Environment temperature:-25℃ ~ +55℃ ◆Comparative humidity:≤95% 	\$12.00	\$11.00
	AI-02(20,30)	<ul style="list-style-type: none"> ◆Can be installed at door>window,passage etc 		\$16.00	\$15.00
	AI-02(40,60)	<ul style="list-style-type: none"> ◆Aptitude judgement,prevent traditionally false alarm 		\$18.00	\$17.00
	AI-04(5,10)	<ul style="list-style-type: none"> ◆The installation height 20cm off ground make the fence not alarm when the intruder is a cat or a dog 		\$20.00	\$19.00
	AI-04(20,30)	<ul style="list-style-type: none"> ◆Anti-cutting function disturbs technology 		\$21.00	\$20.00
	AI-04(40,60)	<ul style="list-style-type: none"> ◆Anti-rain function can be used outdoor of wet places 		\$22.00	\$21.00
	AI-06(5,10)	<ul style="list-style-type: none"> ◆Install and debug easily 		\$23.00	\$22.00
	AI-06(20,30)			\$28.00	\$27.00
	AI-06(40,60)			\$32.00	\$31.00
	AI-2B	<ul style="list-style-type: none"> ◆4 Channel of frequency adjustment mutual active infrared fence detector 	<ul style="list-style-type: none"> ◆Number Of Beams: 2 4 6 8 10 (20 beams max for customer design) ◆Alert Height (mm):360 700 1200 1600 2000 ◆Alert Distance (m):5m 15m 30m 60m 100m ◆Working Voltage: 10.5-15VDC ◆Working Current: ≤50mA ◆Response Time: ≤40ms ◆Alarm Output: NC/NO ◆Contact Capacity: 0.5A/125V AC; 1A/24V DC ◆Tamper Output: NC ◆Contact Capacity: 0.5A/125V AC; 1A/24V DC ◆Working Temperature: -35℃ to +55℃ ◆Beam adjustment: 180 degree wide angle adjustment 	\$20.00	\$20.00
	AI-4B	<ul style="list-style-type: none"> ◆Can be installed at door>window,passage etc 		\$29.00	28.5
	AI-6B	<ul style="list-style-type: none"> ◆Recognize object,can distinguish size of traversing object,will not alarm when the intruder is a cat or a dog 		\$40.00	\$39.50
	AI-8B	<ul style="list-style-type: none"> ◆Anti-cutting function disturbs technology ◆Anti-rain function can be used outdoor of wet places ◆Alarm Indication: Buzzer buzzing 		\$56.00	\$55.00
	AI-10B	<ul style="list-style-type: none"> ◆Install and debug easily 		\$68.00	\$67.00
	AI-2C	<ul style="list-style-type: none"> ◆4 Channel of frequency adjustment active infrared fence detector 	<ul style="list-style-type: none"> ◆Number Of Beams: 2 4 6 8 10 (20 beams max for customer design) ◆Alert Height (mm):360 700 1200 1600 2000 ◆Alert Distance (m):5m 15m 30m 60m 100m ◆Working Voltage: 10.5-15VDC ◆Working Current: ≤50mA ◆Response Time: ≤40ms ◆Alarm Output: NC/NO ◆Contact Capacity: 0.5A/125V AC; 1A/24V DC ◆Tamper Output: NC ◆Contact Capacity: 0.5A/125V AC; 1A/24V DC ◆Alarm Indication: Buzzer buzzing ◆Working Temperature: -35℃ to +55℃ ◆Beam adjustment: 180 degree wide angle adjustment 	\$22.00	\$21.50
	AI-4C	<ul style="list-style-type: none"> ◆Can be installed at door>window,passage etc 		\$29.00	\$28.50
	AI-6C	<ul style="list-style-type: none"> ◆Recognize object,can distinguish size of traversing object,will not alarm when the intruder is a cat or a dog 		\$40.00	\$39.00
	AI-8C	<ul style="list-style-type: none"> ◆Anti-cutting function disturbs technology ◆Anti-rain function can be used outdoor of wet places 		\$58.00	\$57.00
	AI-10C	<ul style="list-style-type: none"> ◆Install and debug easily 		\$69.00	\$68.00
GSM/PSTN Alarm Control Panel					
	AI-GSM01 (GSM&PSTN panel 900/1800MHZ)	<ul style="list-style-type: none"> ◆255 wireless zone,8 wired zone ◆PSTN(land line)& GSM dual-network alarm system ◆LCD display,convenient to operate by keyboard ◆Automatically dial the stored phone numbers and send SMS while alarming ◆One output port to control the external electrical device,such as video camera,light,etc ◆Can connect with alarming monitoring center 	<ul style="list-style-type: none"> ◆Working voltage:DC12V ◆Frequency:315MHZ or 433MHZ GSM frequency:900/1800MHZ ◆Remote control distance:> 100m(open area) ◆Detector emitting distance:100m ◆PIR detection distance:9-12m 	\$93.00	\$92.00
	AI-GSM02 (GSM panel 900/1800MHZ)	<ul style="list-style-type: none"> ◆8 wireless alarm zones,3 wired zones ◆Quad frequency can be used all over the world 	<ul style="list-style-type: none"> ◆Power supply:AC 110-240V/50-60Hz DC 12V/1000mA ◆Frequency:315MHZ or 433MHZ ◆GSM frequency:900/1800MHZ ◆Alarm noise:≥110db 	\$75.00	\$73.00
	AI-GSM02S (GSM panel 850/900/1800/1900MHZ)	<ul style="list-style-type: none"> ◆8 wireless alarm zones,3 wired zones ◆Quad frequency can be used all over the world 	<ul style="list-style-type: none"> ◆Power supply:AC 110-240V/50-60Hz DC 12V/1000mA ◆Frequency:315MHZ or 433MHZ ◆GSM frequency:850/900/1800/1900MHZ ◆Alarm noise:≥110db 	\$60.00	\$58.00








	<div>NEW</div> <div>AI-GSM05 (GSM panel) 850/900/1800/1900MHZ</div>	<ul style="list-style-type: none">◆ 7 wired zones and 99 wireless zones◆ Up to code 8 wireless remote control◆ LCD display, built-in clock, easy and intuitive◆ Full voice guide, easy to operate.◆ Built-in intercom speaker, support external speaker◆ Timing arm and disarm: 3 groups of timing arming, 3 groups of timing disarm.◆ Preset 6 groups of alarm phone automatically dials the telephone voice alarm host.◆ Preset 3 groups SMS phone, send SMS alarm host automatically.	\$50.00	\$49.00	
	<div>NEW</div> <div>AI-GSM06 (GSM&PSTN panel) 850/900/1800/1900MHZ</div>	<ul style="list-style-type: none">◆ Includes 2 wired zones and 99 wireless zones.◆ With dual network of GSM + telephone cable, the System is more secure and reliable.◆ With the quad-band GSM module for global use.◆ Supports code pairing with 8 wireless remote controllers at the most.◆ LCD screen with a built-in clock.◆ With voice prompts for easy operations.◆ Supports 3 groups of timed arming and 3 groups of timed disarming.◆ The main device can dial alarm calls to 6 preset phone numbers and 3 groups of SMS.	\$50.00	\$49.00	
	<div>NEW</div> <div>AI-GSM07 (GSM&PSTN panel) 850/900/1800/1900MHZ</div>	<ul style="list-style-type: none">◆ 4 wired and 10 wireless zones, each can support 10 detectors (the maximum is 100).◆ Display in both Chinese and English language. The built-in clock is convenient for time checking.◆ Original operation system for the main unit allows simple operation.◆ Support card access control system, needless to carry the traditional remote control.◆ Code pairing for up to 8 wireless remote controls.◆ Built-in intercom speakers with high acoustic quality and large volume.◆ Preset 6 alarm phone numbers, which the main unit shall dial automatically to make voice alarm.◆ Preset 3 SMS numbers, to which the main unit shall send the alarm SMS automatically.	\$71.00	\$69.00	
	<div>NEW</div> <div>AI-GSM08 (GSM panel) 850/900/1800/1900MHZ</div>	<ul style="list-style-type: none">◆ 4 wired and 10 wireless zones, each can support 10 detectors (the maximum is 100).◆ Fashionable and high-tech touch keyboard◆ Display in both Chinese and English language. The built-in clock is convenient for time checking.◆ Original operation system for the main unit allows simple operation.◆ Support card access control system, needless to carry the traditional remote control.◆ Code pairing for up to 8 wireless remote controls.◆ Built-in intercom speakers with high acoustic quality and large volume.◆ Arm/disarm at regular time.◆ Preset 6 alarm phone numbers, which the main unit shall dial automatically to make voice alarm.◆ Preset 3 SMS numbers, to which the main unit shall send the alarm SMS automatically.	\$72.00	\$70.00	
	<div>HOT</div> <div>AI-GSM10A (GSM panel) 900/1800MHZ</div>	<ul style="list-style-type: none">◆ 4 wired and 6 wireless defence zones◆ Can preset and store 6 voice phones and 3 message phones◆ Remote two-way intercom◆ Telephone (mobile phone) remote control programming◆ SMS remote control preset & arm/disarm the main panel	<ul style="list-style-type: none">◆ Input Voltage:DC9V~12V◆ Standby Current:<55mA◆ Alarm Current:<450mA◆ Wireless Frequency:315/433◆ GSM Frequency:900/1800MHz◆ Backup Battery:NI-HI AAA*6 DC7.4V◆ Alarm Loudness:110dB	\$29.00	\$27.00
	<div>HOT</div> <div>AI-GSM10B (GSM panel) 850/900/1800/1900MHZ</div>	<ul style="list-style-type: none">◆ The new quad-band GSM module, globally available◆ 4 wired and 6 wireless defence zones◆ Can preset and store 6 voice phones and 3 message phones◆ Remote two-way intercom◆ Telephone (mobile phone) remote control programming◆ SMS remote control preset & arm/disarm the main panel	<ul style="list-style-type: none">◆ Input Voltage:DC9V~12V◆ Standby Current:<55mA◆ Alarm Current:<450mA◆ Wireless Frequency:315/433◆ GSM Frequency:850/900/1800/1900MHz◆ Backup Battery:NI-HI AAA*6 DC7.4V◆ Alarm Loudness:110dB	\$38.00	\$36.00
	AI-TEL01 (PSTN panel)	<ul style="list-style-type: none">◆ It has 100 wireless zone◆ 6 standard wired zone alarm,2 standard outlet to control small appliance◆ Automatic dialing 6 groups of telephone number which pre-setting◆ With the function which can get the first line when alarm◆ With international Contact ID alarm communication format	<ul style="list-style-type: none">◆ Frequency:315MHZ or 433MHZ◆ GSM frequency:900/1800MHZ◆ Remote control distance:> 100m(open area)◆ Detector emitting distance:100m◆ PIR detection distance:9-12m	\$54.00	\$53.00
	AI-TEL02 (PSTN panel)	<ul style="list-style-type: none">◆ 8 wireless zones, 6 wired zones, and 1 output for alarm center◆ Dial 6 groups of phone number automatically◆ Advanced learning code function◆ With super password, project password, and user password three grades for the using rights management◆ With international Contact ID alarm communication format	<ul style="list-style-type: none">◆ Working voltage:AC220V or DC9.6V◆ Alarm current:<10mA◆ Alarm noise:< 100db◆ Working environment:-10℃ ~ +55℃◆ Humidity:≤95% no condensation	\$37.00	\$36.00











Iron box Wired and Wireless Alarm Panel














	AI-238W	<ul style="list-style-type: none"> ◆Support 4 keypads at most ◆Contain keyboard, built-in power supply, recording module, wireless receiving module ◆CONTACT. ID, ADEMC04 + 2 communication protocol ◆5 Arm Mode: leave arm, perimeter arm, sing zone arm, delay arm, remote arm ◆5 zone type: Instant Zone, Delay Zone, 24 Hours Zone, Perimeter Zone, and Bypass Zone ◆Can record the voice for 10 to 20 seconds, proceed voice alarm ◆Can dial 6 groups of telephone number and 1 alarm center telephone number. Trigger alarm, circular dial. ◆Rechargeable 12V, 7Ah battery is optional for you ◆Have "watchdog" function, prevent crashing 	<ul style="list-style-type: none"> ◆Rated Voltage: AC220V±10% ◆Rated Current: ≤50mA ◆Power Consumption: ≤1.5W ◆Siren output: 12VDC, ≤400mA ◆Power Output: 12VDC~15VDC ◆Wireless frequency: 315MHZ ◆Working Temperature: -10°C~55°C ◆Working Humidity: 40%~70% ◆Weight: 3KG ◆Size of iron box: 255mm*235mm*70mm ◆Size of keypad: 159mm*138mm*33mm 	US\$43.00	US\$41.00
	AI-GSM09 (GSM&PSTN panel)	<ul style="list-style-type: none"> ◆Support 8 wired zones, 16 wireless zones ◆Wired zones have adopted a dual-zone technology. ◆Each zone can set as immediately, entrances and exits, internal protection zones, 24 hours, fire alarm, emergency, gas, 24 hours medical, 24 hours hijack, tamper, bell 12 types. ◆12 seconds recording, 6 groups of user's phone 		\$107.00	\$105.00
Wired Alarm Control Panel					
	AI-728	<ul style="list-style-type: none"> ◆High-speed communication format: 12 format contain Ademco Contact ID (report all the codes), Ademco Contact ID (Programmable code), 4+2, Personal Communication etc. 	<ul style="list-style-type: none"> ◆Single-zone connection: (4+2) zone; double zone connection: (8+2) zone ◆Dimension: 140*99.8*1.6 mm 	\$14.50	\$12.50
	AI-728EX	<ul style="list-style-type: none"> ◆Battery Charger: 350mA (AI-728ULT), 360mA (AI-728/728EX) with battery tester ◆AUX power output: 450mA (AI-728ULT), 400mA (AI-728/728EX) 	<ul style="list-style-type: none"> ◆(4+2) zone ◆Dimension: 140*99.8*1.6 mm 	\$14.50	\$12.50
	AI-728ULT	<ul style="list-style-type: none"> ◆Bell Output: 1A, with automatic reset electronic fuse, limiting 3A ◆Metal case and with transformer to be sold separately 	<ul style="list-style-type: none"> ◆Single-zone connection: (4+2) zone; double zone connection: (8+2) zone ◆Dimension: 140*72.6*1.6 mm 	\$14.50	\$12.50
	AI-738	<ul style="list-style-type: none"> ◆Maximun 5 keypads can be connected ◆Telephone line monitoring ◆256 event memory 	<ul style="list-style-type: none"> ◆Single-zone connection: (6+2) zone; double zone connection: (12+2) zone ◆Dimension: 190*86*1.6mm 	\$18.00	\$16.00
	AI-738EX	<ul style="list-style-type: none"> ◆Every defence area with anti-tamper trigger display automatically ◆Battery Charger: 350mA (AI-738ULT), 360mA (AI-738/738EX) with battery tester 	<ul style="list-style-type: none"> ◆(7+2) zone; ◆Dimension: 190*86*1.6mm 	\$18.00	\$16.00
	AI-738ULT	<ul style="list-style-type: none"> ◆AC power input: AC16.5V, 3A, 50-60HZ ◆Metal case and with transformer to be sold separately 	<ul style="list-style-type: none"> ◆Single-zone connection: (8+2) zone; double zone connection: (16+2) zone ◆Dimension: 190*72.5*1.6mm 	\$24.00	\$22.00
	AI-748	<ul style="list-style-type: none"> ◆Maximun 5 keypads can be connected ◆Telephone line monitoring ◆High-speed communication format ◆Every defence area with anti-tamper trigger display automatically 	<ul style="list-style-type: none"> ◆Single-zone connection: (12+2) zone; double zone connection: (24+0) zone ◆Dimension: 190*101.5*1.6 mm 	\$35.00	\$30.00
	AI-748EX	<ul style="list-style-type: none"> ◆Battery Charger: 360mA with battery tester ◆AUX power output: 1000mA ◆Bell Output: 1A ◆AC power input: AC16.5V, 3A, 50-60HZ ◆Metal case and with transformer to be sold separately 	<ul style="list-style-type: none"> ◆(12+2) zone ◆Dimension: 190*101.5*1.6 mm 	\$35.00	\$30.00
	Metal case	Metal case with transformer for 728/738/748 series	◆Dimension 280*250*81mm	\$11.00	\$10.00
	AI-636	<ul style="list-style-type: none"> ◆Built-in one zone input ◆Adjustable brightness ◆Can set four doorbell zone 	◆Size: 143*78*23 mm	\$6.00	\$5.00
	AI-646	<ul style="list-style-type: none"> ◆3 groups of emergency alarm button ◆Low power consumption (20mA) ◆Defence zone fault monitoring ◆Fireproof housing 	◆Size: 135*97*32 mm	\$6.00	\$5.00
Passive Infrared Detector					













	<p>AI-P85 (Outdoor detector with pet immunity) 100% waterproof and fireproof material</p>	<p>◆PIR intrusion detector integrating the most advanced security technology ◆It adopts 2 dual PIR sensors with high accuracy, intelligent digital chip, make an accurate judgment of true intruder or other interference that can cause wrong alarm ◆And it is with function of automatic memory of environmental change ◆Prevent effectively the interference caused by a 25 kg past or 10 cats, insect, mouse, birds etc.</p>	<p>◆Working voltage: DC9-16V ◆Working current: 30mA 12VDC ◆Detection Range: 11.6m*11.6m ◆Alarm output: NC.100mA/28VDC ◆Installation height: 2m-2.7m ◆Anti white light resistance: >20000LUX ◆Anti-EMI/RFI: 10V/m(10MHz-1000MHz) ◆Motion test: 0.2m/s-3.5m/s(0.6ft-11ft) ◆Size: 176*85*69mm</p>	\$21.00	\$19.60
	<p>AI-P806W (Wide angle)</p>	<p>◆IP65 waterproof ◆Two PIR and MW detection tech ◆Automatic setting of anti-masking ◆Microwave synchronization ◆Detector mode: EI-OR-AND ◆Selectable detection sensitivity ◆Alternative Led OFF ◆Anti white light ◆Solid relay output</p>	<p>◆Power supply: 9-16VDC ◆Coverage: 12m*12m 110° ◆Install height: 1.5m~2.4m ◆MW frequency: 10.525GHz ◆Size: 160*65*50.5mm</p>	\$26.00	\$25.00
	<p>AI-P806T (Pet immune)</p>		<p>◆Pet immunity: 25kg ◆Power supply: 9-16VDC ◆Coverage: 12m*12m 110° ◆Install height: 1.5m~2.4m ◆MW frequency: 10.525GHz ◆Size: 160*65*50.5mm</p>	\$27.00	\$26.00
	<p>AI-P806C (Curtain)</p>		<p>◆Detecting angle: 10 degree</p>	\$26.00	\$25.00
	<p>AI-P301 (Curtain PIR detector)</p>	<p>◆Indoor curtain PIR detector ◆Type of sensor: dual lower-noise infrared sensor ◆Output alarm: NC/NO optional ◆LED ON/OFF optional ◆Adopt SMT design, enhance the ability of diamagnetic ◆Alarm output: NC/NO optional Contact capacity: 28VDC, 100mA</p>	<p>◆Working voltage: DC10V~16V ◆Working current: ≤20mA (DC12V) ◆Detection distance: 6m/11m optional ◆Detection angle: 15 degree ◆Mounting height: 1.8m~2.5m (suggest 2m) ◆Size: 110mm*69mm*41mm</p>	\$5.10	\$4.60
	<p>AI-P127 (Curtain PIR detector)</p>	<p>◆Indoor curtain PIR detector ◆Type of sensor: dual low noise pyroelectric infrared sensor ◆Auto temperature compensation ◆Resisting white light strength >6500LUX ◆Alarm output: NC/NO optional ◆LED ON/OFF optional ◆Mounting : wall mounted</p>	<p>◆Working voltage: DC10V~16V ◆Detection distance: 6m/11m optional ◆Detection angle: 15 degree ◆Mounting height: 1.8m~2.5m (suggest: 2m) ◆Alarm output: NC/NO optional, contact capacity: 28VDC, 100mA ◆Size: 94mm*49mm*35mm</p>	\$5.90	\$5.40
	<p>AI-P526 (Wide angle PIR detector)</p>	<p>◆Indoor wide angle PIR detector ◆Type of sensor: dual low noise pyroelectric infrared sensor ◆Anti white light strength >6500LUX ◆Alarm output: NC/NO optional ◆Pulse counting 1P/2P optional ◆LED ON/OFF optional ◆Mounting: wall mounted</p>	<p>◆Working voltage: DC10V~16V ◆Working current: ≤20mA (DC12V) ◆Detection distance: 12m ◆Detection angle: 100 degree ◆Mounting height: suggest 2.2m ◆Alarm output: NC/NO optional Contact capacity: 28VDC, 100mA ◆Size: 90mm*62mm*44mm</p>	\$6.60	\$6.10
	<p>AI-P55 (PIR detector)</p>	<p>◆New streamlined design ◆Low noise, high sensitivity, anti-electromagnetic interference ◆Fully protected and sealed optical lenses, anti-mosquito interference ◆Easy installation with lock, ease of construction</p>	<p>◆Detection distance: 14m ◆Working voltage: 9-15VDC ◆Working current: 14mA ◆Installation height: 2.2m-3.0m ◆Anti-white light interference ≥ 8000LUX ◆Anti-EMI: 30V/M(10MHz-1000MHz) ◆Alarm output: NC</p>	\$4.50	\$4.00
	<p>AI-P476</p>	<p>◆Low noise, high sensitivity, dual source infrared sensor ◆Ideal for residential, anti-theft ◆Automatic temperature compensation ◆Anti EMI: Metal shield RFI ◆Lens: 2nd generation Fresnel lens</p>	<p>◆Power input: 9-16VDC ◆Mounting height: 2-2.7m ◆Working environment temperature: -10℃ ~ +50℃ ◆Relative humidity: 5% ~ 95% RH ◆Alarm output: NC, 28VDC 0.15A ◆Size: 93 * 67 * 52mm</p>	\$3.50	\$2.90
	<p>AI-P101 (PIR & Microwave detector)</p>	<p>◆Adopting doppler effect + energy analysis ◆Microwave adopting X-Band plane antenna ◆Auto temperature compensation function ◆Anti white light strength >6500LUX ◆LED ON/OFF optional ◆Adopting SMT design, superhigh ability of diamagnetism ◆LED indicating: green is infrared; yellow is microwave; red is alarm</p>	<p>◆Working voltage: DC10V~16V (DC10V~24V optional) ◆Detection distance: 12m ◆Detection angle: 100 degree ◆Mounting: wall mounted ◆Mounting height: suggest 2.2m ◆Alarm output: NC/NO optional; Contact capacity: 28VDC, 100mA ◆Size: 135mm*66mm*64mm</p>	\$9.10	\$8.60
	<p>AI-P7225 (PIR & Microwave detector)</p>	<p>◆Indoor infrared with microwave detector ◆With excellent capacity of anti-false alarm ◆Simple and quick installation ◆Built-in temperature compensation and microwave anti-interference function ◆Durable ABS shell, excellent anti-shock function</p>	<p>◆Operating voltage: 7.5~16VDC ◆Detection distance: 7.6m ◆Microwave frequencies: 24.125GHz ◆Anti-tamper output: NC 50mA, 24VDC ◆Relative humidity: 5% ~ 95% RH ◆Anti Anti-white light: 8000LUX ◆Size: 119*71*42mm</p>	\$7.80	\$7.30





	AI-P75 (PIR with pet immunity)	<ul style="list-style-type: none"> ◆Stable performance, greatly reduce the occurrence of false positives ◆Two independent anti-polarity dual source infrared sensor ◆Automatic temperature compensation ◆Automatically adjust of pulses 	<ul style="list-style-type: none"> ◆Detect distance: 11m × 11m ◆Input power: 11 to 16VDC ◆Installation height: 2m to 2.7m ◆Environment temperature: -10 °C ~ +50 °C ◆Alarm Output: NC28Vdc; 0.15A ◆Size: 68×127×52mm 	\$9.00	\$8.50
	AI-RV971 (Vibration sensor)	<ul style="list-style-type: none"> ◆Photoelectric vibration sensor ◆Sensitivity is adjustable ◆Microprocessor design improves false alarm immunity ◆Tamper immunity ◆Alarm indication 	<ul style="list-style-type: none"> ◆Operating voltage: 9 to 16VDC ◆Operating current: 15mA ◆Alarm contact: NC, 12VDC, 100mA max ◆Tamper contact: NC, 12VDC, 100mA max ◆Dimension: 26*85*24mm 	\$4.00	\$3.30
 	AI-542-1 (Wall Vibration Detector)	<ul style="list-style-type: none"> ◆Sonic vibration sensor detection ◆Special filtering technology to prevent false alarm effectively ◆Vibration sensing and vibration analysis integration, ensure detection accuracy ◆Adjustable sensitivity, apply to RC wall, Masonry wall ◆Double anti-tamper protection, prevent vandalism effectively ◆Signal line can install the stainless steel or wind hose, can prevent vandalism effectively ◆Compact size, stable performance, easy installation, safety and reliability ◆Low-power, energy-saving, lead-free material, green Initiative 	<ul style="list-style-type: none"> ◆Detection method: acoustic sense ◆Detection range: RC wall 0.5 m (radius), brick wall 1 to 1.5 meters (radius) ◆Operating voltage: 9 ~ 16VDC ◆Operating Current: 15mA DC12V ◆Alarm contact: C.NC.NO Contact capacity 0.1A 24VDC ◆Anti-tamper contact: NC Contact rating 0.1A 24VDC ◆Alarm Time: ATut 2.2 seconds ◆Working temperature: -20 °C ~ 50 °C ◆Storage temperature: -20 °C ~ 60 °C ◆Installation: surface mounted ◆Color: gray, black, white ◆Dimensions: 114×34×24mm (L×W×H) 	\$6.50	\$6.00
 	AI-542 (Bank Vault Vibration Detector)	<ul style="list-style-type: none"> ◆Acoustic vibration sensor to detect ◆Apply to a variety of environments, materials ◆Special filtering technology to effectively prevent false positives ◆Vibration sensing and vibration analysis are integrated, which improve the detection results ◆Adjustable sensitivity ◆Vibration detection and dual anti-tamper function can effectively prevent vandalism ◆Using anti-sAItage unit for signal lines ◆Magnetic suction device, iron products are easy to install ◆Small size, excellent performance, fast installation, secure and reliable ◆Lead-free materials, green 	<ul style="list-style-type: none"> ◆Detection method: Acoustic sensors ◆Detection range: 3 m radius of steel plate, 3.5 m radius of flat glass ◆Operating Voltage: 9~16VDC ◆Operating Current: 15mA DC12V ◆Alarm contacts: C.NC.NO; Contact capacity: 0.1A 24VDC ◆Tamper contacts: NC; Contact capacity: 0.1A 24VDC ◆Alarm time: ATut 2.2 seconds ◆Operation temperature: -20° C~50° C ◆Storage temperature: 20° C~60° C ◆Mounting: Surface mounted ◆Color: Grey, black, white ◆Size: 114×34×24mm (L×W×H) ◆Weight: 43g 	\$9.50	\$9.00
	AI-P456 (Glass-break detector)	<ul style="list-style-type: none"> ◆Software driven, 8/12 bit microprocessor-controlled digital signal processing ◆High frequency sound pressure detection ◆Full audio spectrum 7 frequency signal and impact analysis including infra-sound pressure analysis ◆Unique acoustic microphone chamber and casing design 	<ul style="list-style-type: none"> ◆Detection distance: 9m ◆Working voltage: 9-16VDC ◆Working current: 18MA ◆Working temperature: -10 °C ~ +50 °C ◆Alarm output: NC 28VDC 0.15A ◆Size: 90x66x25mm 	\$4.00	\$3.50
 	AI-522 (Audio Glass Break Detector)	<ul style="list-style-type: none"> ◆Installation distance is up to 9M ◆Ceiling installation and wall-installation are all reliable ◆Can detect common flat glass, tempered glass, laminated glass, metallic sprayed coating glass ◆All types of glass can detect the smallest area of 30CM × 30CM ◆Glass thickness: flat glass 3.2mm~4mm, tempered glass 6.4mm, laminated glass 6.4mm, metallic sprayed coating glass 6.4mm ◆Light source: Infrared LED 	<ul style="list-style-type: none"> ◆Power supply: DC11~15V nonpolarity ◆Current consumption: 40mA Max ◆Detection distance: 9M ◆Rated Current: 25mA max DC12V ◆Rated voltage: 9.3~16V DC ◆Alarm output: C.NC.NO Dry contact ◆Alarm contact: NC, 24V DC, 50mA ◆Tamper contact: NC, 24V DC, 0.5A ◆Audio sensors: Omnidirectional microphone ◆Operating temperature: 0°C ~ +50°C ◆Storage Temperature: - 20°C~60°C ◆Color: creamy-white ◆Size: 119*74*26mm ◆Net Weight: 90g 	\$14.00	\$13.00
 	AI-021 (Glass Break Detector)	<ul style="list-style-type: none"> ◆Connecting to control panel without additional power source, detecting audio frequency vibration of breaking glass ◆High waterproof ◆Two kinds of adjustment for sensitivity ◆It can also detect the break when glass cutter is cutting ◆Suit for 2mm~20mm thickness intensity or special glass ◆Material of line: PU ◆Material: ABS 	<ul style="list-style-type: none"> ◆Conducting resistance: 7Ω ◆Open circuit time on alarm: ≥3sec ◆Triggering resistance: ≥1MΩ ◆Operation temperature: -20°C~80°C ◆Max current: 18VDC 70mA ◆Max voltage: 18VDC ◆Weight: 40g ◆Installing position: at a corner of the glass, where is 10cm far from the frame or side. ◆Detection range: 3m diagonal distance for stronger sensitivity; 1.5m diagonal distance for weaker sensitivity 	\$5.50	\$4.70

	AI-P465 (Ceiling detector)	<ul style="list-style-type: none"> ◆ Low noise, high sensitivity, dual source infrared sensor ◆ Suitable for ceiling mount, ideal for residential security use ◆ Secondary automatically adjust the number of pulses ◆ Automatic temperature compensation; ◆ Flame-retardant shell ◆ Anti EMI: metal shield RFI 	<ul style="list-style-type: none"> ◆ Input power: 9—16VDC, 18mA ◆ Alarm display: red LED, constant light for 3 seconds ◆ Lens: Fresnel lens ◆ Detection Range: 7.5m*6m (Installation height 2.4m) ◆ Alarm output: NC. 150mA/28VDC ◆ Operating temperature: -10℃ ~ +50℃ ◆ Size: Φ108*35mm 	\$5.00	\$4.00
Smoke Detector					
	AI-S031 (Independent type)	<ul style="list-style-type: none"> ◆ Dedicated chip signal processing, and more energy efficient, more stable ◆ Alarm output: sound and light alarm ◆ Infrared photoelectric sensor ◆ Anti-electromagnetic interference ◆ Be able to adapt to changes in the environment ◆ Dust and pest proof, anti-white light interference 	<ul style="list-style-type: none"> ◆ Operating voltage: 9V battery ◆ Standby current: <15μA ◆ Alarm current: <30mA ◆ Operating Humidity: ≤95% RH ◆ Detection area: 20 m² ◆ Sensitivity: 2.06% ft ◆ SPL: 85 dB / 3m (10ft) ◆ Size: Φ107 * 36MM 	\$4.50	\$4.00
	AI-S032 (Independent type)	<ul style="list-style-type: none"> ◆ Power supply non-polar input ◆ Infrared photoelectric sensor ◆ MCU processing, eliminate false alarm ◆ Alarm output: Sound & Flash alarm ◆ SMT manufacture technology, high stability ◆ Dustproof, mothproof, anti-light interference design ◆ Anti-RFI(20V/m-1GHz) 	<ul style="list-style-type: none"> ◆ Operating voltage: 9V battery ◆ Static current: 12uA ◆ Alarm current: 10mA ◆ Sound level: 85dB/3m ◆ Installation: Ceiling mounted ◆ Sensitivity: 2.06%ft±1.3%ft ◆ Working environment: -10℃~+50℃, (≤95%RH No congelation) ◆ Dimension: Φ100*43mm 	\$6.40	\$5.90
	AI-S041 (Wired networking type)	<ul style="list-style-type: none"> ◆ Power interrupt reset / automatic reset optional ◆ Non-polarity power input ◆ Alarm indication: red LED on ◆ Alarm output NO / NC optional ◆ SMT technology, strong stability ◆ Metallic shield, good anti-interference(20v/m-1GHz) 	<ul style="list-style-type: none"> ◆ Operating voltage: DC 12-30V ◆ Operating temperature: -10℃ to +50℃ ◆ Operating Humidity: ≤95% RH ◆ Detection area: 80 m² ◆ Size: Φ103*53mm (with base) 	\$5.00	\$4.50
Heat Detector					
	AI-H01 (Wired networking type)	<ul style="list-style-type: none"> ◆ Low standby current. ◆ Anti-EMI and Anti-RFI. ◆ Adopt SMT and Double Sided Glass Fiber circuit board. ◆ Heating-up temperature alarm (8-15/minute). ◆ LED visible in 360 degrees direction. 	<ul style="list-style-type: none"> ◆ Operating voltage: DC 9V-35V. ◆ Alarm Current: 22mA@DC12V, 40mA@DC24V. ◆ Static current: 50uA; ◆ Constant temperature alarm 135F(57C). ◆ Alarm Output: LED indicator, Relay output. ◆ Dimension: Φ100*55mm. 	\$6.00	\$5.50
	AI-H02 (Wired networking type)	<ul style="list-style-type: none"> ◆ Low standby current. ◆ Anti-EMI and Anti-RFI. ◆ Adopt SMT and Double Sided Glass Fiber circuit board. ◆ Heating-up temperature alarm (8-15/minute). ◆ Alarm Output: LED indicator, Relay output. ◆ LED visible in 360 degrees direction. 	<ul style="list-style-type: none"> ◆ Operating voltage: DC 9V-35V ◆ Alarm current: 22mA@DC12V, 40mA@DC24V ◆ Static current: 50uA; ◆ Constant temperature alarm 135(57) ◆ Dimension: Φ100*48mm. 	\$6.40	\$5.90
	AI-H03 (Wired networking type)	<ul style="list-style-type: none"> ◆ Low standby current. ◆ Anti-EMI and Anti-RFI. ◆ Adopt SMT and Double Sided Glass Fiber circuit board. ◆ Heating-up temperature alarm (8-15/minute). ◆ Alarm Output: LED indicator, Relay output. ◆ LED visible in 360 degrees direction. 	<ul style="list-style-type: none"> ◆ Operating voltage: DC10V-35V ◆ Alarm current: 600mAh ◆ Static current: ≤100uA; ◆ Constant temperature alarm 135(57) ◆ Dimension: Φ103*53mm. 	\$5.50	\$5.00
Gas Leakage Detector(LPG and Natural Gas)					
	AI-G033 (Wired type)	<ul style="list-style-type: none"> ◆ Wired gas leakage detector ◆ Ceiling mounted ◆ Relay output alarm ◆ High Reliability sensor ◆ MCU processing adopted, SMT adopted, good stability ◆ MAIunction auto-check indicator 	<ul style="list-style-type: none"> ◆ Operating voltage: DC12-24V ◆ Alarm level: 10% ±5% LEL ◆ Alarm output: Sound & Flash ◆ Execute criterion: GB15322; EN50194; UL1484 ◆ Dimension: Φ104*51mm 	\$5.70	\$5.20
	AI-G011 (Wired networking type)	<ul style="list-style-type: none"> ◆ Alarm output: relay output + sound and light alarm + electromagnetic pulse output ◆ Adopt micro-processing and SMT technology, good stability ◆ MAIunction auto-check indicator ◆ Executive standard: GB15322; EN50194; UL1484 	<ul style="list-style-type: none"> ◆ Operating voltage: AC 220V ◆ Alarm current: <120mA ◆ Gas species: LPG and natural gas ◆ Alarm level: 10% ± 5% LEL ◆ Equipped with accessories: electromagnetic valve or manipulator ◆ Size: 115 * 73 * 46 mm 	\$7.60	\$7.30

	AI-G012 (Wired networking type)	<ul style="list-style-type: none"> Alarm output: relay output + sound and light alarm+electromagnetic pulse output Adopt micro-processing and SMT technology, good stability MAIunction auto-check indicator Executive standard: GB15322; EN50194; UL1484 	<ul style="list-style-type: none"> Operating voltage: DC12-24V Alarm current: <120mA Gas species: LPG and natural gas Alarm level: 10% ± 5% LEL Equipped with accessories: electromagnetic valve or manipulator Size: 115 * 73 * 46 mm 	\$7.00	\$6.50
	AI-G013 (Independent type)	<ul style="list-style-type: none"> Alarm output: relay output + sound and light alarm+electromagnetic pulse output Adopt micro-processing and SMT technology, good stability MAIunction auto-check indicator Executive standard: GB15322; EN50194; UL1484 	<ul style="list-style-type: none"> Operating voltage: AC 220V Standby current: <70mA Gas species: LPG and natural gas Alarm level: 10% ± 5% LEL Equipped with accessories :electromagnetic valve or manipulator Size: 115 * 73 * 46 mm 	\$7.50	\$7.00
	AI-G031 (Wired networking type)	<ul style="list-style-type: none"> Installation way:ceiling mounted Alarm output: relay output + sound and light alarm+electromagnetic pulse output Adopt micro-processing and SMT technology, good stability Executive standard: GB15322; EN50194; UL1484 	<ul style="list-style-type: none"> Operating voltage: AC 220V Alarm current: <120mA Gas species: LPG and natural gas Alarm level: 10% ± 5% LEL Equipped with accessories: electromagnetic valve or manipulator Size: Φ116*44 mm 	\$8.50	\$8.00
	AI-G016 (Wired gas leakage alarm)	<ul style="list-style-type: none"> Wired gas leakage detector Wall mounted; Alarm:Relay output Auto reset; High Reliability sensor; MCU processing adopted, SMT adopted, good stability MAIunction auto-check indicator 	<ul style="list-style-type: none"> Operating voltage: 12-24V DC; Alarm output: Sound&Flash Alarm level: 10% ±5% LEL. Dimension: 110*70*40mm . 	\$6.50	\$6.00
Carbon Monoxide Detector					
	AI-C022 (Independent type)	<ul style="list-style-type: none"> Standby current:<15μA Alarm current:<30mA Operating temperature: -10℃ to +50℃ Operating Humidity≤ 95% RH Detection area: 20 m2 SPL: 85 dB / 3m (10ft) Size: Φ106* 53MM 	<ul style="list-style-type: none"> Power supply:AC110-265V, 9V back-up battery 	\$7.00	\$6.50
	AI-C032 (Independent type)	<ul style="list-style-type: none"> Standby current:<15μA Alarm current:<30mA Operating temperature: -10℃ to +50℃ Operating Humidity≤ 95% RH Detection area: 20 m2 SPL: 85 dB / 3m (10ft) Size: Φ107* 36MM 	<ul style="list-style-type: none"> Power supply:AC110-265V, 9V back-up battery 	\$6.50	\$6.00
	AI-C033 (Wired networking type)	<ul style="list-style-type: none"> Auto-reset after alarm MCU processing adopted MAIunction auto-check indicator Alarm output N.C. / N.O. Optional Be able to work with electrovalve /exhaust fan SMT adopted, excellent stability Alarm indicator: Red LED flash MAIunction indicator: Yellow LED on & Beeper long-buzz 	<ul style="list-style-type: none"> Operating voltage: DC 12V-24V Rated power: ≤3W (220V AC power supply) Warm-up time: 3-5 minutes Alarm level: 100 PPM of CO Alarm sound: ≥70dB (within 1 meter) Dimension: 115*72*41mm 	\$14.00	\$13.00
	AI-C034 (Wired networking type)	<ul style="list-style-type: none"> Auto-reset after alarm MCU processing adopted MAIunction auto-check indicator Alarm output N.C. / N.O. Optional Be able to work with electrovalve /exhaust fan SMT adopted, excellent stability Alarm indicator: Red LED flash MAIunction indicator: Yellow LED on & Beeper long-buzz 	<ul style="list-style-type: none"> Operating voltage:AC 85-265V Rated power: ≤3W (220V AC power supply) Warm-up time: 3-5 minutes Alarm level: 100 PPM of CO Alarm sound: ≥70dB (within 1 meter) Dimension: 115*72*41mm 	\$14.80	\$13.80
Alarm Accessories					
	ES-626 (Siren)	<ul style="list-style-type: none"> Independent high tone horn design,large alarm volume Beautiful appearance,loud voice,suitable for installation in corridors,windows and other places. 	<ul style="list-style-type: none"> Rated voltage: DC12V Working voltage:9~13VDC Working current:280~480mA Rated Power:15W Sound pressure: 110±3DB Size:106*100*110mm (with bracket) 	\$2.00	\$1.50
	ES-628 (Siren)		<ul style="list-style-type: none"> Rated Voltage: 12VDC Operationg Voltage :6-15 VDC Rated Current:320/600 /1200 mA Power out:15W / 20W SPL (Db/m): 105~123 dB Product size: 77*80*100mm 	\$2.00	\$1.60

	ES-629 (Siren)		<ul style="list-style-type: none"> ◆ Rated Voltage: 12VDC ◆ Operating Voltage: 6-15VDC ◆ Rated Current: 600mA ◆ SPL: 110±3 Db ◆ Product Size: 110*55*110mm ◆ Resistance: 8Ω ◆ Housing Material: ABS ◆ Output Power: 15W ◆ Sound Source Two kind of alarm 	\$3.40	\$2.90
	103 (Indoor siren with strobe)	<ul style="list-style-type: none"> ◆ Streamlined design, with decorative ◆ Common red lights setting, strong deterrence ◆ ABS case, with certain fire-retardant properties ◆ Variety of installation options, flexible and convenient 	<ul style="list-style-type: none"> ◆ Rated voltage: DC12V ◆ Working voltage: 9~13VDC ◆ Working current: 150~250mA ◆ Flashing frequency: 150 beats / min ◆ Sound pressure: 110±3DB ◆ Size: 122.5 * 73.5 * 47.5mm 	\$2.00	\$1.60
	AI-95LED (Siren and Strobe)	<ul style="list-style-type: none"> ◆ Input voltage: 12V DC ◆ Operating Current: 90 mA (siren + flashing lights) 25 mA (strobe) ◆ Continuous siren test: Over 4 hours ◆ Continuous flash test: over 1000 hours ◆ Sound: Siren sounds ◆ Alarm output: 110 ± 5 dB (at 1 foot) ◆ Material: ABS ◆ Color: ivory white + red 		\$3.60	\$3.10
	LM-110 (A pair)		<ul style="list-style-type: none"> ◆ Rated Voltage: 12VDC ◆ Rated Current: ≤750mA ◆ Working voltage current range: 6-15VDC ◆ Size: 75*170mm 	\$10.20	\$9.20
	LM-105 (Strobe)		<ul style="list-style-type: none"> ◆ Rated current: 100mA ◆ Rated voltage: 12VDC ◆ Stroboscopic number ◆ Size: 73*73*45 mm 	\$2.00	\$1.60
	LM-107 (Outdoor siren with strobe)		<ul style="list-style-type: none"> ◆ Housing material: PC/white ◆ Operating voltage: 6-18VDC ◆ Related voltage: 12VDC ◆ Rated current: 300mA ◆ SPL Db/1M: 115 ◆ Without battery ◆ Size: 210*130*78mm 	\$6.00	\$5.50
	LM-106 (Outdoor siren with strobe)		<ul style="list-style-type: none"> ◆ Power supply voltage: 13.8 to 14.2VDC ◆ UV prevention, Metal cover inside ◆ Flash rate: 120 times/minute ◆ SPL: 120db/m ◆ Sound type: single tone ◆ Without battery ◆ Size: 270L*193W*100Hmm 	\$12.00	\$11.50
	AI-DB001 (Wireless doorbell)	<ul style="list-style-type: none"> ◆ Audio: 38 sources to choose from, through an external touch button operation. Sources including Asia, Europe, America and the Middle East world-known music. ◆ Volume control: high, medium, and low volume options, through an external switch (or key) operation. ◆ LED indication: LED will be on after AC receiver power on, LED also flashes regularly with the music after the door bell rang; after AC doorbell powered LED is not lit, to achieve energy-saving purposes, LED also flashes regularly with the music after door bell rang. ◆ The four doorbell used battery for power, for shipping reasons, battery will not be provided for samples 		\$4.00	\$3.50
	AI-DB001C (Digital doorbell) one-to-one not interference			\$6.10	\$5.60
	AI-DB002 (Wireless doorbell)			\$5.90	\$5.40
	AI-EB01	<ul style="list-style-type: none"> ◆ Emergency button and exit button ◆ ABS Housing ◆ Alarm Output: NO and NC Output ◆ Color: white 	<ul style="list-style-type: none"> ◆ Voltage: 12 or 24V DC ◆ Carrying current: 0.3A ◆ Size: 76 * 17 * 17mm 	\$1.20	\$1.00
	AI-EB02	<ul style="list-style-type: none"> ◆ Panic Button with Key, emergency button ◆ Color: White ◆ ABS Housing ◆ Output: NO and NC 	<ul style="list-style-type: none"> ◆ Voltage: 12 or 24V DC ◆ Carrying current: 0.3A ◆ Size: 86 x 86 x 32mm 	\$0.90	\$0.70
	AI-EB02-1	<ul style="list-style-type: none"> ◆ Panic Button with Key, emergency button ◆ Color: White ◆ ABS Housing ◆ Output: NO and NC 	<ul style="list-style-type: none"> ◆ Voltage: 12 or 24V DC ◆ Carrying current: 0.3A ◆ Size: 50 x 50 x 32mm 	\$0.80	\$0.60

	AI-120 (Emergency Push Button)	<ul style="list-style-type: none">◆ Locking can be manually reset Design◆ It has long life and can be reused, and switches can be used more than 10 million times◆ NO.NC output, Maximum contact capacity: 3A.125VAC◆ Operating temperature:-10℃~+60℃◆ Contact resistance: less than 0.2Ω◆ Size: 73mm × 33mm × 24.8mm (L × W × H)◆ Panel Size: 121mm × 70mm (L × W)◆ Usage method: After pressing the button, then reset, pry two sides of the buttons with small slotted screwdriver	\$3.00	\$2.80	
	AI-140A (Emergency Button With Lamp GUYED)	<ul style="list-style-type: none">◆ Patent documented and trustworthy◆ Double emergency button, can pull and press, safe and reliable◆ Indicator display, with a buzzer, allowing security visible and hearable◆ Exposed design, suitable for used in a variety of places◆ Special mask design, light display more softer when normally◆ DC12V power, NC.NO contact output, match and protect panel wire connection	<ul style="list-style-type: none">◆ Power Supply: DC 12V ± 10%◆ Current Consumption: 40mA maximum◆ Usual Current Consumption: 10mA◆ Alarm Output: Yellow COM, White NC, Green NO◆ Wiring: Red +, Black -, Yellow COM, White NC, Green NO◆ Alarm Display: Red LED flashes◆ Sound Alarm: Intermittent buzzer hint◆ Alarm Lifted: pull again or press again◆ Material: ABS engineering plastics◆ Color: Milk white◆ Weight: 60g	\$9.50	\$9.00
	AI-EB03		<ul style="list-style-type: none">◆ Working voltage: 12/24VDC◆ Power: 10W◆ Switch state: NC/NO (single or dual)◆ Size: 87mm*87mm*51mm	\$2.30	\$2.00
	AI-MC01 (Surface mount)	<ul style="list-style-type: none">◆ Excellent surface magnetic contact◆ Housing: fireproof ABS◆ Colour: white	<ul style="list-style-type: none">◆ Gap: 13-19mm◆ Output: N.C. N.O. & changeover available◆ Size: 64*19*12.8mm◆ Packing: 10SETS/PE bag	\$0.65	\$0.45
	AI-MC02 (Surface mount)	<ul style="list-style-type: none">◆ Excellent surface magnetic contact◆ Housing: fireproof ABS◆ Colour: white	<ul style="list-style-type: none">◆ Gap: 15-25mm◆ Output: N.C◆ Size: 50*14*12mm◆ Packing: 10SETS/PE bag	\$1.00	\$0.80
	AI-MC07 (Surface mount)	<ul style="list-style-type: none">◆ Surface mounetd magnetic contact◆ ABS housing ,ideal for wooden door or window◆ Output: N.C. N.O. & changeover available	<ul style="list-style-type: none">◆ Gap: 15-25mm available on request◆ Dimension: 64*19*13mm◆ Packing: 10SETS/PE bag	\$0.82	\$0.62
	AI-MC03 (Recessed)	<ul style="list-style-type: none">◆ Excellent recessed magnetic contact◆ Housing: ABS ,white◆ Output: N.C	<ul style="list-style-type: none">◆ Gap: 15-25mm available on request◆ Size: Φ10*18.5mm◆ Packing: 20SETS/PE bag	\$0.80	\$0.60
	AI-MC10 (Recessed)	<ul style="list-style-type: none">◆ Excellent Recessed Magnetic Contact◆ Contact: N.C. N.O. & changeover available◆ Housing: ABS◆ Colour: white /brown	<ul style="list-style-type: none">◆ Gap: 20-30mm◆ Dimension: Φ19*25mm◆ Packing: 10SETS/PE bag	\$1.00	\$0.80
	AI-MC21 (Iron magnetic)	<ul style="list-style-type: none">◆ Housing: Alloy-Zn, grey◆ Output: NC, NO or Changeover available◆ Leads: 1007UL22AWG530mm, wire with cable available	<ul style="list-style-type: none">◆ Gap: 40-60mm, 50-60mm available◆ Dimension: 106*16*16mm	\$4.00	\$3.80
	AI-MC04 (Roller shutter)	<ul style="list-style-type: none">◆ Roller shutter magnetic contact◆ Contact switch: N.C. N.O. & changeover available◆ Housing: Metal (Alloy-Al), grey	<ul style="list-style-type: none">◆ Gap: 50 to 70mm◆ Remarks: 4 screws included◆ Packing: 1sets/bag	\$3.20	\$3.00
	AI-MC25 (Roller shutter)	<ul style="list-style-type: none">◆ Magnetic contact for Metal door /rolling door◆ Contact switch: N.C. N.O. & changeover available◆ Metal case (alloy zinc), surface mounted type◆ Inner packing: 1sets/bag	<ul style="list-style-type: none">◆ Operating distance: 50 to 70mm◆ Power: 10W◆ Voltage: 100V◆ Current: 0.5A	\$5.60	\$5.40
Bank ATM Series Products					
	AI-606 (Bank ATM use)	<ul style="list-style-type: none">◆ Exclusive use for Bank ATM as front-end alarm host◆ 2-way vibration analysis, a road block timing◆ 3 independent dry contact relay outputs◆ 1 Road siren output, by pressing a button lift◆ Support backup battery connection◆ with RS 485 output, easy to use real-time monitoring or machine networking◆ relay output lock can be released by pressing a button			

	 AI-580 (Reflective Sensor for ATM)	<ul style="list-style-type: none">◆Detection range: 1-50mm◆Light source: 940nm Infrared light-emitting diodes◆Reaction time: 50ms/150ms/300ms/500ms Optional◆Alarm type: Light, MOS relay, normally open normally closed, shock capacity: 0.1A/350V◆operating voltage: 9-16VDC (Polarity protection)◆Power consumption: 20Ma(under 12VDC)◆operating temperature: -20℃-50℃◆Connecting cable: 500m Control box and sensor head connection cable	\$135.00	\$133.00	
	 AI-10R (Vibration Sensor for ATM)	<ul style="list-style-type: none">◆Small and unobtrusive◆It Can be used in any closed-circuit system◆It has anti-tamper switch◆Adjustable contact pressure◆Easy to install◆Material: a.Contact: silver-plated detector contact, nickel-plated Anti-sAltage contacts b.Housing: ABS resin, Gray	<ul style="list-style-type: none">◆Loop structure: NC◆Circuit : 0.1A 50VDC◆Contact capacity: 5W Max◆Contact resistance: When the terminal contact pressure is more than 5g, the contact resistance is less than 100mΩ◆Contact pressure: 5g to 25g adjustable, usually 19g ± 3g◆Operation temperature: -10℃~50℃◆Life: More than one hundred thousand times◆Size: 56×21×17mm(L×W×H)◆Weight: 21g	\$5.50	\$5.00
TERMS:	NO NEED MOQ				
PACKING: :	ALL BE PACKED IN OUR STANDARD PACKING				
PAYMENT:	T/T IN ADVANCE				
REMARK:	BASED ON EXW				